

Mains cable

Mains cable Copper unshielded , 300/300 V



FEATURES:

Light duty cable

For use with light portable appliances

Class 5 flexible copper conductor according to BS EN 60228

SPECIFICATION:

Cable type	Mains cable
Wire Code	H03VV-F
Conductor	Copper
Shielding	unshielded
Conductor insulation	PVC
Original packaging	100 m
Sheath	PVC
Min. bending radius, not moving	6 x line ϕ
Temperature range	-5...+70 °C

PRODUCT RANGE:

Art. no.	Cross-section	Cores	Sheath colour	Core colours	ϕ Sheath
RND 475-00010	0.50 mm ²	2	black	blue/brown	5 mm
RND 475-00011	0.50 mm ²	2	white	blue/brown	5 mm
RND 475-00012	0.75 mm ²	2	black	blue/brown	5.5 mm
RND 475-00013	0.75 mm ²	2	white	blue/brown	5.5 mm
RND 475-00014	0.50 mm ²	3	black	blue/brown/green/yellow	5.3 mm
RND 475-00015	0.50 mm ²	3	white	blue/brown/green/yellow	5.3 mm
RND 475-00016	0.75 mm ²	3	black	blue/brown/green/yellow	5.8 mm
RND 475-00017	0.75 mm ²	3	white	blue/brown/green/yellow	5.8 mm