

Mains cable

Mains cable Copper unshielded , 300/500 V white



FEATURES:

Indoor general wiring cable

For use in public areas

Class 5 flexible copper conductor according to BS EN 60228

SPECIFICATION:

Cable type	Mains cable
Wire Code	H05Z1Z1-F
Conductor	Copper
Sheath colour	white
Shielding	unshielded
Conductor insulation	LSZH
Original packaging	100 m
Sheath	LSZH
Min. bending radius, not moving	5 x line ϕ
Temperature range	-20...+60 °C

PRODUCT RANGE:

Art. no.	Cross-section	Cores	Core colours	ϕ Sheath
RND 475-00053	0.75 mm ²	2	blue/brown	6.3 mm
RND 475-00054	1.00 mm ²	2	blue/brown	6.6 mm
RND 475-00055	1.50 mm ²	2	blue/brown	7.4 mm
RND 475-00056	0.75 mm ²	3	blue/brown/green/yellow	6.7 mm
RND 475-00057	1.00 mm ²	3	blue/brown/green/yellow	7 mm
RND 475-00058	1.50 mm ²	3	blue/brown/green/yellow	8 mm
RND 475-00059	2.50 mm ²	3	blue/brown/green/yellow	9.9 mm
RND 475-00060	0.75 mm ²	4	blue/brown/green/yellow/grey	7.3 mm
RND 475-00061	1.00 mm ²	4	blue/brown/green/yellow/grey	7.9 mm
RND 475-00062	1.50 mm ²	4	blue/brown/green/yellow/grey	9 mm
RND 475-00063	2.50 mm ²	4	blue/brown/green/yellow/grey	10.8 mm