

Control cable unshielded

Flexible Control Cables, RND



FEATURES:

Interconnecting cable for measuring, controlling or regulation in control equipment for assembly and production lines, conveyors and for computer units

Suitable for fixed installations or for flexible use in conditions of light mechanical stress

Can be used outdoors when protected against direct sunlight, and in dry or moist conditions indoors

Class 5 flexible copper conductor according to BS EN 60228

Fixed: -40°C to +70°C

SPECIFICATION:

Cable type	Control cable
Conductor	Copper
Sheath colour	grey
Shielding	unshielded
Conductor insulation	PVC
Original packaging	50 m
Halogen-free	No
Sheath	PVC

PRODUCT RANGE:

Art. Nr.	Cross-section	Cores	Sheath	Core colours
RND 475-002500	0.50 mm ²	2	5.2 mm	black, numbered
RND 475-002510	0.75 mm ²	2	5.7 mm	black, numbered
RND 475-002521	1.00 mm ²	2	5.9 mm	black, numbered
RND 475-002531	1.50 mm ²	2	7.1 mm	black, numbered
RND 475-002540	0.50 mm ²	3	5.5 mm	black, numbered/black, numbered/green/yellow
RND 475-002550	0.75 mm ²	3	6 mm	black, numbered/black, numbered/green/yellow
RND 475-002561	1.00 mm ²	3	6.2 mm	black, numbered/black, numbered/green/yellow
RND 475-002571	1.50 mm ²	3	7.5 mm	black, numbered/black, numbered/green/yellow
RND 475-002582	2.50 mm ²	3	9 mm	black, numbered/black, numbered/green/yellow
RND 475-002594	4.00 mm ²	3	10.9 mm	black, numbered/black, numbered/green/yellow
RND 475-002606	6.00 mm ²	3	12.4 mm	black, numbered/black, numbered/green/yellow
RND 475-002610	0.50 mm ²	4	5.9 mm	black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002620	0.75 mm ²	4	6.5 mm	black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002631	1.00 mm ²	4	7 mm	black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002641	1.50 mm ²	4	8.2 mm	black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002652	2.50 mm ²	4	9.8 mm	black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002664	4.00 mm ²	4	11.9 mm	black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002676	6.00 mm ²	4	13.6 mm	black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002680	0.50 mm ²	5	6.5 mm	black, numbered/black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002690	0.75 mm ²	5	7.4 mm	black, numbered/black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002701	1.00 mm ²	5	7.6 mm	black, numbered/black, numbered/black, numbered/black, numbered/green/yellow

Art. Nr.	Cross-section	Cores	Sheath	Core colours
RND 475-002711	1.50 mm ²	5	9.2 mm	black, numbered/black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002722	1.50 mm ²	5	11 mm	black, numbered/black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002734	1.00 mm ²	5	13.1 mm	black, numbered/black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002746	1.00 mm ²	5	15.1 mm	black, numbered/black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002750	1.75 mm ²	7	8 mm	black, numbered/black, numbered/black, numbered/black, numbered/black, numbered/black, numbered/black, numbered/green/yellow
RND 475-002761	1.00 mm ²	7	8.5 mm	black/green-yellow
RND 475-002771	1.50 mm ²	7	10 mm	black/green-yellow