



VINYL-INSULATED (EASY ENTRY) RING TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14	12	10
AMP.	9	12	17	18	30	35	50

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL: VINYL

INSULATION COLOR:

22-16A.W.G.: RED ■ 16-14A.W.G.: BLUE ■

12-10A.W.G.: YELLOW ■

TERMINAL MATERIAL: COPPER

WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE	DIMENSION inch(mm)								Q'TY BOX
	BRAZED SEAM	BUTTED SEAM		d2	W	F	L	E	D	d1	T	
12-10 A.W.G. 4-6 mm ²	RVEB5-3.7	RVE5-3.7	#6	0.146 3.7	0.283 7.2	0.24 6.1	0.937 23.8	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEBS5-4	RVES5-4	#8	0.169 4.3	0.283 7.2	0.24 6.1	0.937 23.8	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEBL5-4	RVEL5-4	#8	0.169 4.3	0.374 9.5	0.327 8.3	1.067 27.1	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEB5-5	RVE5-5	#10	0.209 5.3	0.374 9.5	0.327 8.3	1.067 27.1	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEB5-6	RVE5-6	1/4	0.252 6.4	0.472 12	0.413 10.5	1.205 30.6	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEBM5-6	RVEM5-6	1/4	0.252 6.4	0.472 12	0.512 13	1.303 33.1	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEB5-8	RVE5-8	5/16	0.331 8.4	0.591 15	0.524 13.3	1.382 35.1	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEB5-10	RVE5-10	3/8	0.413 10.5	0.591 15	0.524 13.3	1.382 35.1	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEB5-12	RVE5-12	1/2	0.512 13	0.756 19.2	0.63 16	1.563 39.7	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEB5-14	RVE5-14	9/16	0.591 15	1.26 32	0.992 25.2	2.177 55.3	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEB5-16	RVE5-16	5/8	0.669 17	1.26 32	0.992 25.2	2.177 55.3	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	RVEB5-20	RVE5-20	3/4	0.827 21	1.26 32	0.992 25.2	2.177 55.3	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500

