Samsung SSD 850 PRO

Data Sheet, Rev.2.0 (January, 2015)



Summary

- SATA 6Gb/s SSD for Client PCs
- 2.5 inch form factor
- Samsung 3-core MEX controller
- Samsung 3D V-NAND MLC
- Up to 1GB Samsung Low Power DDR2 SDRAM cache memory
- Samsung Magician Software for SSD management
- Samsung Data Migration Software

shrinking form factors. This architecture results in higher density and higher performance using a smaller footprint. Samsung's 3D V-NAND technology is a breakthrough in overcoming the density limits currently faced with the conventional planar NAND architecture.

The Samsung SSD 850 PRO is a brand new successor of the 840 PRO, Samsung's premium SSD product. The 850 PRO is powered by Samsung's 3D V-NAND technology. In 2013, Samsung mass-produced 3D V-NAND products for datacenters which have already been proved in the market. And Samsung is now releasing the world's 1st 3D V-NAND SSD for client PCs.

3D V-NAND Technology and THE SAMSUNG SSD 850 PRO

Samsung's 3D V-NAND flash memory is fabricated using an innovative vertical design. Its vertical architecture stacks cell-layers on top of one another rather than trying to decrease the cells' length and width to fit today's ever-

Ultimate Read/Write Performance

Powered by Samsung's own cutting-edge 3D V-NAND technology, the 850 PRO delivers up to twice the write speed than that of the traditional 2D planar NAND flash for ultimate read and write performance. By changing to the layer



cylindrical cell structure, more cells can be stacked vertically, resulting in smaller footprint and higher density. As a result, you gain superior maximum read and write performance in both sequential and random aspects, especially with the 128GB model that outperforms other similar models in the market by more than 100MB/s in write speed.

Plus, with RAPID mode, you can boost its optional higher speeds - up to almost twice faster write performance speeds than those of the previous model. The Magician software allows you to enhance performance by processing data on a system level using free PC memory (DRAM) as a cache.

Enhanced Endurance and Reliability

Enhanced endurance

With twice the endurance of a typical NAND flash SSD, the 850 PRO will keep working as long as you use it. Samsung's 3D V-NAND technology is built to handle 150 Tera Bytes Written (TBW) for 128GB and 256GB, 300 TBW for 512GB and 1TB. Plus, it comes with an industry-leading tenyear limited warranty.

Advanced data encryption

The 850 PRO provides the same data encryption features as the 840 EVO does. The Self-Encrypting Drive (SED) security technology will help keep your data safe at all times. It includes an AES 256-bit hardware-based encryption engine to ensure that your personal files remain secure. A hardware-based encryption engine secures your data without performance degradation that you may experience with a software-based encryption. Also, the 850 PRO is compliant with advanced security management solutions (TCG Opal and IEEE 1667). Magician will guide you through "How to use security features". Furthermore, users can delete or initialize data with the crypto erase service with PSID.

Efficient Power Management

Less Power consumption for active and stand-by states

Even with all of the above performance improvements, advances in the design of the MEX Controller and the use of the new technology of 3D V-NAND have enabled us to make the 850 PRO as one of the most energy-efficient drives on the market. Its idle power is almost the same as the 840 PRO's and its active (average) write power has been dramatically reduced up to 40% due to the 3D V-NAND technology.

Moreover, when DEVSLP is enabled, the power consumption of 850 PRO is below 2mW.



Technical Specifications

Samsung SSD 850 PRO				
Usage Application	Client PCs			
Capacity	128GB, 256GB, 512GB,1TB(1,024GB)			
Dimensions(LxWxH)	100 x 69.85 x 6.8 (mm)			
Interface	SATA 6Gb/s (compatible with SATA 3Gb/s and SATA 1.5Gb/s)			
Form Factor	2.5 inch			
Controller	Samsung 3-core MEX Controller			
NAND Flash Memory	Samsung 3D V-NAND MLC			
DRAM Cache Memory	256MB (128GB) or 512MB(256GB&512GB) or 1GB (1TB) LPDDR2			
	Sequential Read:	Max. 550 MB/s		
	Sequential Write:	Max. 520 MB/s (256GB/512GB/1TB)		
		Max. 470 MB/s (128GB)		
Performance*	4KB Random Read (QD1):	Max. 10,000 IOPS		
	4KB Random Write(QD1):	Max. 36,000 IOPS		
	4KB Random Read(QD32):	Max. 100,000 IOPS		
	4KB Random Write(QD32):	Max. 90,000 IOPS		
TRIM Support	Yes (Requires OS Support)			
Garbage Collection	Yes			
S.M.A.R.T	Yes			
Security	AES 256-bit Full Disk Encryption (FDE)			
	TCG/Opal V2.0, Encrypted Drive(IEEE1667)			
Weight	Max. 66g (1TB)			
Reliability	MTBF: 2 million hours			
TBW	128/256GB: 150 Terabytes Written(TBW)			
	512GB/1TB: 300 TBW			
Power	Active Read (Average): Max. 3.3W(1TB)			
	Active Write (Average): Max. 3.0W(1TB)			
Consumption	Idle: Max. 0.4W			
	Device Sleep: 2mW	0°C to 70°C		
Temperature	Operating: Non-Operating:	-40°C to 85°C		
Humidity	5% to 95%, non-condensing			
Vibration	Non-Operating: 20~2000Hz, 20G			
Shock	Non-Operating: 1500G, duration 0.5msec, 3 axis			
Warranty	10 years limited			

^{*} Sequential performance measurements based on CrystalDiskMark v.3.0.1.Random performance measurements based on lometer 2010. Performance may vary based on SSD's firmware version, system hardware & configuration. Test system configuration: Intel Core i5-2500K @ 3.3GHz, DDR3 1600MHz 4GB, OS – Windows7 Ultimate x64 SP1 IRST 11.5.4.1001, MS performance guide pre-condition Intel® Z68

^{**} Power consumption measured with IOmeter 1.1.0 version with Intel i7-4770K, Samsung DDR3 8GB, Intel® DH87RL OS-Windows7 Ultimate x64 SP1



Product Lineup

Density	Model Name	Box Contents	Model Code
128 GB*	MZ-7KE128	Samsung SSD 850 PRO 128GB Warranty statement Installation guide Software CD	MZ-7KE128BW MZ-7KE128B/KR MZ-7KE128B/CN
256 GB*	MZ-7KE256	Samsung SSD 850 PRO 256GB Warranty statement Installation guide Software CD	MZ-7KE256BW MZ-7KE256B/KR MZ-7KE256B/CN
512 GB*	MZ-7KE512	Samsung SSD 850 PRO 512GB Warranty statement Installation guide Software CD	MZ-7KE512BW MZ-7KE512B/KR MZ-7KE512B/CN
1TB(1,024GB*)	MZ-7KE1T0	Samsung SSD 850 PRO 1TB Warranty statement Installation guide Software CD	MZ-7KE1TOBW MZ-7KE1TOB/KR MZ-7KE1TOB/CN

^{*} GB: 1GB = 1,000,000,000 bytes. A certain portion of capacity may be used for system file and maintenance use, thus the actual capacity may differ that indicated on the product label.

For more information, please visit www.samsung.com/ssd. To download the latest software & manuals, please visit <a href="www.samsung.com/sam

DISCLAIMER

SAMSUNG ELECTRONICS RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are for reference purposes only. All information discussed herein may change without notice and is provided on an "AS IS" basis, without warranties of any kind. This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted by one party to the other party under this document, by implication, estoppels or otherwise. Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply. For updates or additional information about Samsung products, contact your nearest Samsung office.

COPYRIGHT © 2015

This material is copyrighted by Samsung Electronics. Any unauthorized reproductions, use or disclosure of this material, or any part thereof, is strictly prohibited and is a violation under copyright law.

TRADEMARKS & SERVICE MARKS

The Samsung Logo is the trademark of Samsung Electronics. Adobe is a trademark and Adobe Acrobat is a registered trademark of Adobe Systems Incorporated. All other company and product names may be trademarks of the respective companies with which they are associated.

