






Subracks - *europac*PRO ServicePLUS

Front horizontal rails

Order Information

 <p style="text-align: right; font-size: small;">bza44980</p>		<p style="text-align: center;">"light" Type L-OD without lip</p>  <p style="text-align: center; font-size: x-small;">06197006</p>	<p style="text-align: center;">"light" Type L-KD short lip</p>  <p style="text-align: center; font-size: x-small;">06197007</p>	<p style="text-align: center;">"heavy" Type H-KD short lip</p>  <p style="text-align: center; font-size: x-small;">06197008</p>	<p style="text-align: center;">"heavy" Type H-LD long lip</p>  <p style="text-align: center; font-size: x-small;">06197009</p>
<p>With HP markings from 28 HP, Al extrusion, anodised finish, conductive contact surface</p>		<p>Al extrusion, anodised finish, conductive contact surface, with printed HP markings</p> <p style="text-align: center;">without lip: 2 x 3 U installation and continuous 6 U front panel</p>	<p>Al extrusion, anodised finish, conductive contact surface, with printed HP markings</p> <p style="text-align: center;">short lip: horizontal rail and front panel form a single plane</p>	<p>Al extrusion, anodised finish, conductive contact surface, with printed HP markings</p> <p style="text-align: center;">short lip: horizontal rail and front panel form a single plane</p>	<p>Al extrusion, anodised finish, conductive contact surface, with printed HP markings</p> <p style="text-align: center;">long lip: for insertion/extraction of CompactPCI or VME64x boards</p>
Usable length HP	Length mm	1 piece (SPQ 10)¹⁾	1 piece (SPQ 10)¹⁾	1 piece (SPQ 10)¹⁾	1 piece (SPQ 10)¹⁾
20	106.68	34560-020	34560-120	34560-220	34560-320
28	147.32	34560-028	34560-128	34560-228	34560-328
40	208.28	34560-040	34560-140	34560-240	34560-340
42	218.44	34560-042	34560-142	34560-242	34560-342
63	325.12	34560-063	34560-163	34560-263	34560-363
84	431.80	34560-084	34560-184	34560-284	34560-384
–	1000	34560-001	34560-101	34560-201	34560-301
Screw, M4 x 14, PU 100 pieces		24560-130	24560-130	24560-130	24560-130
Screw, M4 x 10, required if guide rails are screwed to slot 1, PU 100 pieces		–	–	24560-155	24560-155
Threaded inserts see page		6.33	6.33	6.33	6.33

¹⁾ SPQ (standard pack quantity): Part number includes 1 piece, but delivery is exclusively made in standard pack quantity (SPQ); please order at least the SPQ quantity or a multiple
"light": loading capacity up to approx. 7.5 kg; "heavy": loading capacity > 7.5 kg

Note

- 1000 mm version without M4 thread to front, without printed markings and without notch for 19"-bracket
- Rugged horizontal rails with 3 fixing holes see section "Rugged Subracks", page 6.99