




Subracks - *europac*PRO ServicePLUS

Guide rails for plug-in units and modules, one-piece, groove width 2 mm and 2.5 mm

Order Information

Assembly			For plug-in units and frame type plug-in units standard type			standard type, with DIN connector fixing		
- can be clipped into Al extruded horizontal rails - can be clipped into 1.5 mm thick plates Storage temperature from -40 °C ... 130 °C								
			up to 220 mm length, PBT, UL 94 V-0; from 280 mm length, multi-piece, end piece PBT, UL 94 V-0, central section Al extrusion			PBT, UL 94 V-0		
			PU 10 pieces ²⁾			1 piece (SPQ 50) ¹⁾		
			PU 10 pieces ²⁾			1 pair (SPQ 10) ¹⁾		
Board length mm	Groove width mm	Colour mm						
70	2	red	–		34579-230	–		
70	2	grey	–		34579-231	–		
160	2	red	24560-351		64560-001	64560-074		
220	2	red	24560-353		64560-002	64560-075		
280	2	red	24560-379		–	–		
340	2	red	24560-380		–	–		
160	2.5	red	–		64560-096	–		
220	2.5	red	–		64560-098	–		

Accessories

Retention screw, PU 100 pieces; Torque max. 0.2 Nm 	24560-141	–	24560-141
ESD clip, PU 50 pieces	24560-255		24560-255

1) SPQ (standard pack quantity): Part number includes 1 piece, but delivery is exclusively made in standard pack quantity (SPQ); please order at least the SPQ quantity or a multiple

2) Part no. includes one packing unit (PU); delivery is exclusively made in PU

Description of accessories see from page 6.41