

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_N-50-3-51/133\_N



### Description

Straight cable plug for semi-rigid cable

Interface standards

IEC 60169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 18 GHz

#### Mechanical Data

Centre contact plugged  
Outer contact soldered  
Weight 0.0435 kg

#### Environmental Data

Operating Temperature -55 °C to 70 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	Air Dielectric - Bead - PPH
Coupling nut	Brass

##### Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

#### Related Documents

Catalogue drawing	DOU-00007863
Assembly instruction	DOC-0000180866

#### Ordering Information

Single package	11_N-50-3-51/133_NE
----------------	---------------------

#### Additional Information

Suitable cable	EZ_141_TP_M17
----------------	---------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**