


ORTAC METAL CABLE GLANDS SERIES



TECHNICAL DETAILS
Material

Cap nut	: Brass with nickel plated
Sealing ring	: Silicone
Gland body	: Brass with nickel plated
O-ring	: Silicone
Connection thread	: Metric (EN60423)/PG (DIN 40430)
Protection class	: IP68 - 5 bar
Temperature range	: -40 °C +100 °C

Properties

Highor low temperature resistance
 Smooth surface
 Easy to assemble
 Halogen free

METAL CABLE GLANDS STANDARD TYPE SILICONE SEAL


SİLİKON CONTALI ETANJ PİRİNÇ RAKOR

Hammaddesi	: Pirinç, nikel kaplı
Bağlantı dişi M	: EN 60423
Bağlantı dişi PG	: DIN 40430
Koruma sınıfı	: IP68 - 5 bar
Isıya direnci	: -40 °C + 100 °C
Conta	: Silikon
O-ring	: Silikon


METRIC/PG THREAD CABLE GLANDS
PRODUCT RANGE OVERVIEW

AG Thread	Code	H mm	GL mm	B mm	C mm	Ø mm
M 12 x 1,5	MBGS 01	22	6	14	14	3 - 6,5
M 16 x 1,5	MBGS 02	23	7	18	17	4 - 8
M 20 x 1,5	MBGS 03	26,5	8	22	22	6 - 12
M 25 x 1,5	MBGS 04	28	8	27	24	10 - 14
M 32 x 1,5	MBGS 05	31,5	9	34	30	13 - 18
M 40 x 1,5	MBGS 06	38	9	43	40	18 - 25
M 50 x 1,5	MBGS 07	43	9	55	50	22 - 32
M 63 x 1,5	MBGS 08	48	14	68	64	33 - 34
PG 7	PBGS 01	22	6	14	14	3 - 6,5
PG 9	PBGS 02	23	6	17	17	4 - 8
PG 11	PBGS 03	24,5	6	20	20	5 - 10
PG 13,5	PBGS 04	26,5	6,5	22	22	6 - 12
PG 16	PBGS 05	28	6,5	24	24	10 - 14
PG 21	PBGS 06	31,5	7	30	30	13 - 18
PG29	PBGS 07	38	8	40	40	18 - 25
PG36	PBGS 08	43	10	50	50	22 - 32
PG42	PBGS 09	47	12	57	57	30 - 38
PG48	PBGS 10	48	14	64	64	34 - 44

IP 68

Halogen free