

**VG MS ZE (standard brass cable gland strain relief)
VGM63-MS54 ZE**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Cable gland with external concentric strain relief
(clamping jaws), IP 54

General ordering data

Type	VGM63-MS54 ZE
Order No.	1778530000
Version	VG MS ZE (standard brass cable gland strain relief), Cable glands, M 63, 10 mm, OD min. 35 - OD max. 45 mm, IP65, Brass, nickel-plated
GTIN (EAN)	4032248161546
Qty.	5 Stück

Erstellungs-Datum September 28, 2020 3:11:57 PM CEST

Katalogstand 11.09.2020 / Technische Änderungen vorbehalten

VG MS ZE (standard brass cable gland strain relief) VGM63-MS54 ZE

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Dimensions and weights

Length	54 mm	Length (inches)	2.126 inch
Net weight	464.3 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General information

Material	Brass, nickel-plated	Cable glands	metric
External thread	M 63	Pitch of thread	1.5 mm
Length of thread	10 mm	AF size 1	68 mm
AF size 2	66 mm	Protection degree	IP54
Protection degree with GWDR	IP65	Operating temperature range, min.	-20 °C
Operating temperature range, max.	80 °C	Outer cable diameter, min.	35 mm
Outer cable diameter, max.	45 mm	Clamping range, strain relief, min.	35 mm
Clamping range, strain relief, max.	48 mm	Halogen	No
Seal insert	NBR	Torque for cap nut, min.	13.33 Nm
Torque for cap nut, max.	13.33 Nm	Torque for connecting adapter, min.	20 Nm
Torque for connecting adapter, max.	20 Nm		

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
eClass 9.0	27-14-44-32	eClass 9.1	27-14-44-32
eClass 10.0	27-14-44-32	UNSPSC	30-21-18-01

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN, WSCAD