



A powerful, durable and reliable workhorse whose reputation is built on helping you build yours. It's been rigorously tested, beaten up, dropped and pushed to the limits to make sure it will always work when you need it most. The 2235 Series is incredibly powerful, durable and reliable so that it delivers every time you need REAL WORK done right.

- 1 220 Nm (900 ft-lb) of maximum torque in reverse - that's the best-in-class performance.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Titanium hammercase is lightweight with unparalleled durability.
- Unique reverse-bias 7-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Patented technology reduces the noise level without sacrificing the power.
- FREE two-year limited warranty without tool registration.

Specifications at 6.2 bar (90 psi)

Part Number	2235QTIMAX
Ordering number	47517574001
Drive size (square)	1/2 in
Torque settings (forward / reverse)	4 / 1
Other available versions:	
- bare tool	2235QTIMAX-2
- kit with 10 short sockets	2235QTIMAX-10SK
- kit with 3 long sockets	2235QTIMAX-3SK

PERFORMANCE

Maximum torque in forward	870 ft-lb / 1 180 Nm
Maximum torque in reverse	900 ft-lb / 1 220 Nm
Nut busting torque in reverse	1 300 ft-lb / 1760 Nm
Recommended fastener size	9/16 in / M14
Free speed	8 500 rpm
Impacts per minute	1 220

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	6.0 CFM / 170 L/min
Air consumption at load	24.0 CFM / 680 L/min
Impacting sound pressure / power (ISO15744)	91.9 / 102.9 dB(A)
Free speed sound pressure / power (ISO15744)	88.7 / 99.7 dB(A)
Vibration level / measurement uncertainty (ISO28927)	9.0 / 2.8 m/s ²

WEIGHT & DIMENSIONS

Tool weight	4.7 lb / 2.1 kg
Tool dimensions (L x W x H)	193 x 74 x 183 mm
Shipping weight	5.5 lb / 2.5 kg
Shipping dimensions (L x W x H)	216 x 244 x 82 mm
UPC / EAN code	6 63023 11999 1
Origin	Assembled in the USA





SK4M3L
81287377
1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)



SK4M14
81287351
1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)



Impact sockets
For the complete range, see our accessory catalogue.



BMD5-4
92842087
Cable balancer, 2-4 kg, 2 m (6-1/2 ft)



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



115-LBK1
04616108
Lubricant kit for Impacttools™ with composite housing



115-4T
04616157
Grease for Impacttools with composite housing



2235-THK1
47517319001
Impact mechanism service kit



SK4M5L
81287369
1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)



SK4M18
81287385
1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)



4UA9
03070216
1/2" right-angle head (speed reduction: 25% torque output reduction: up to 50%)



2235M-BOOT
47520153001
Protective tool boot



10Z4
03875671
Oil, Class 1, no. 10, 0.12 L



Lubricants
For the complete range, see our accessory catalogue.



2235-TK1
47517401001
Motor service kit

0