



Klemsan®

334120 AVK 2,5/4T

2,5-4mm², screw type, single deck earth terminal block for AVK series, Insulation material PA, Yellow-Green

General Product Information	Insulating material	PA 66
	Inflammability class acc. to UL 94	V2
Dimensions	Width	6 mm
	Length	42.00 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	44.50 mm
TSE / CE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4 mm ²
	Norm	EN 60947-7-2
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4 mm ²
	VDE Norm	EN 60947-7-1/EN 60947-7-2
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	6 mm ²
	Minimum fine Strand cross section	0.5 mm ²
	Maximum fine strand cross section	6 mm ²
	AWG Conductor Range	20-10
	Connection Type	screw/vidal

Insulation Stripping length	10 mm
Tightening torque	0.5/0.8 Nm

Insulated Screwdrivers



- IKT 3
(3,5x100mm)-Isolated screwdriver - 3,5x100 mm



- MR 35x15-



- MR 35x7,5-



- MR 35x7,5 (1 m.)-



- MR 35x7,5 (30 cm.)-

Mounting Rails



- MR 32-



- MR 35x15 (1 m.)-



- MR 35x7,5-



- MR 35x7,5 (2 m.)-

End Brackets



- KD 3-



KD 4-



KD 7-

Group Markings

Unprinted Terminal Markers



GE-Group Label



DG 10 / 6-10 x 6

MR 32/MR35

Labeling (UNPRINTED)



ATOM - ATOM Certificate

ATOM - ATOM Certificate

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Avrupa standartlarına uygunluk belgesi - CE Certificate

Avrupa standartlarına uygunluk belgesi - CE Certificate

UL Sertifikası - UL Certificate

Norveç onaylı denizcilik sektöründe kullanılabilirlik belgesi - DNV Certificate

EAC - Russian EAC

AutoCat File

AutoCat File

AutoCat File

Order Info

334120 2,5-4mm²,screw type,single deck earth terminal block for AVK series,Insulation material PA,Yellow-Green

