## **Kuhnke Technical Data**



The following page(s) are extracted from multi-page Kuhnke product catalogues or CDROMs and any page number shown is relevant to the original document. The PDF sheets here may have been combined to provide technical information about the specific product(s) you have selected.

Hard copy product catalogues, and CDROMs have been published describing Kuhnke Pneumatics, Solenoids, Relays and Electronics; some divided into different books. A list of current publications is available on this web site or from our sales offices. Some may be available for download, but as substantially larger files.

## **Contact Details**

Kuhnke sales and service in the UK

H. Kuhnke Ltd Unit 6 Focus 303 Focus Way, Walworth Business Park Andover Hampshire SP10 5NY United Kingdom

Tel: +44 (0)1264 364194 Fax: +44 (0)1264 365991 Email: sales@kuhnke.co.uk


### **Important Note**


The information shown in these documents is for guidance only. No liability is accepted for any errors or omissions. The designer or user is solely responsible for the safe and proper application of the parts, assemblies or equipment described.


# Directional Control Valves (5/2), Solenoid Operated, ISO

Valves are constructed to the European ISO standard permitting interchangeability between manufacturers. ISO valves have a standard mounting configuration. Valves are also available with a European automotive standard coil configuration (CNOMO).

	Size	Туре	Catalogue Number	
Description			Poppet Design	Spool Design
Single Solenoid		Outboard coil	76087-91-00	76083-91-00
Spring Return-	ISO-1	Coil on top	76087-94-00	76083-94-00
air assisted		CNOMO Coil	76087-97-00	76083-97-00
	ISO-2	Outboard coil		
		Coil on top		
1.2		CNOMO Coil	76097-97-00	76093-97-00
Double Solenoid	ISO-1	Outboard coil	76087-92-00	76083-92-00
With Detent		Coil on top	76087-95-00	76083-95-00
		CNOMO Coil	76087-98-00	76083-98-00
	ISO-2	Outboard coil		
513		Coil on top		
		CNOMO Coil	76097-98-00	76093-98-00
Double Solenoid		Outboard coil		
With Priority	<b>ISO-1</b>	Coil on top	76087-96-00	
Detent		CNOMO Coil		
	ISO-2	Outboard coil		
		Coil on top		
513		CNOMO Coil		
Single Solenoid		Outboard coil		
External Air Pilot *	ISO-1	Coil on top		
Spring Return		CNOMO Coil	76387-97-00	76383-97-00
\$\frac{1}{2} \\ \frac{1}{5} \\ \frac{1}{3} \\ \frac	ISO-2	Outboard coil	76397-97-00	76393-97-00
		Coil on top		
		CNOMO Coil		
Double Solenoid External Air Pilot *	ISO-1	Outboard coil		
		Coil on top		
Detent		CNOMO Coil	76387-98-00	
	ISO-2	Outboard coil		76393-98-00
513		Coil on top		
313		CNOMO Coil		







#### **Order Coils Separately**

Valve catalogue numbers do not include solenoid coils. Coils are supplied loose and unmounted as separate items. (Double solenoid types require 2 coils.)

Std. AC Coil Cat. No. 76410-02-\*\*
Std. DC Coil Cat. No. 76410-00-\*\*
CNOMO AC Coil Cat. No. 76411-02-\*\*
CNOMO DC Coil Cat. No. 76411-00-\*\*

\*\* - Add the required coil voltage suffix code from the chart below to complete the coil catalogue number.

<u>Voltage</u>	<u>AC</u>	DC
12V	_	01
24V	12	02
48V	13	03
110V	14	04
230V	15	05

<sup>\*</sup>External Air Pilot: valves have an auxilliary port for connecting a separate air pilot supply for the solenoid section. Use when switching air pressures below 2.5 bar.

For technical details of ISO valves contact factory. See accessory section for manifolds and sub bases.