



## GML 209 NJ LED 24 HH schwarz/black

Industrial Connectors:Rectangular connectors GDM-series:Type B Industrial standard:Cable socket with electronic insert

### Delivery informations

Availability available  
 Document created at 18.06.2008


### Product description

Description function indicator (LED) with protective circuit (diode)  
 Type GML 209 NJ LED 24 HH schwarz/black  
 Order No. 933 389-100  
 Other standard types transparent housing,  
 cable gland grey: Order No. 933 389-106  
 Number of contacts 2 + PE  
 Cable gland PG 9 (black)  
 Conductor size max. 1.5 mm<sup>2</sup>  
 Standard industrial standard (11 mm)  
 Housing Color transparent  
 Construction type B

### Description of Wiring

LED color LED red  
 Suppressor diode  
 Other characteristics correct polarity must be ensured

### Drawing



### Technical data

Pin dimensions	6.3 mm x 0.8 mm
Rated voltage	DC 24 V
Rated current	8 A
Contact resistance	<= 4 mOhm
Type of termination	screw / cable shoe / cable eye
Suitable cables	4.5 mm to 7 mm diameter
Mounting	central screw
<b>Material</b>	
Contact surface material	Sn
Contact bearer material	PA
Housing material	PA
<b>Environmental conditions</b>	
Protection class (IEC 60529)	IP 65
Pollution severity	3
Temperature range	-40 °C to +90 °C
<b>Inflammability class</b>	
Housing	94 V-1
Contact bearer	94 HB
<b>Approvals</b>	
UR	UR
VDE	VDE
<b>Packing unit</b>	
Packaging unit	50 pieces
<b>Scope of delivery and accessories</b>	
Accessories to order separately	(NBR) flat gasket GM 207-3, Order No. 731 423-002; knurled screw GDM 3011-8, Order No. 732 574-001; stainless steel screw GDM 3011 RF-1, Order No. 734 363-001