



### Overview

Model Name	APC Back-UPS 1100VA, 230V, AVR, Schuko Sockets, CIS
Includes	CD with software , User Manual , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	Armenia , Azerbaijan , Belarus , Georgia , Kazakhstan , Moldova, Republic Of , Mongolia , Russian Federation , Tajikistan , Turkmenistan , Ukraine , Uzbekistan

### Output

Output Power Capacity	660 Watts / 1100 VA
Max Configurable Power (Watts)	660 Watts / 1100 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Connections	(4) Schuko CEE 7 (Battery Backup)

### Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	Schuko CEE 7/7P
Cord Length	1.16 meters
Input voltage range for main operations	150 - 280 V
Maximum Input Current	5 A
Input Breaker Capacity	10 A

### Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	8 hour(s)
Replacement Battery	APCRBC113

RBC Quantity	1
--------------	---

## Communications & Management

Interface Port(s)	USB
Available SmartSlot™ Interface Quantity	0
Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rating	273 joules
Data Line Protection	RJ-11 Modem/Fax/DSL protection (two wire single line)

## Physical

Maximum Height	215.0 mm
Maximum Width	130.0 mm
Maximum Depth	336.0 mm
Rack Height	0 U
Net Weight	12.0 kg
Shipping Weight	12.94 kg
Shipping Height	295.0 mm
Shipping Width	245.0 mm
Shipping Depth	440.0 mm
Master Carton Units	1.0
Master Carton Weight	0.0 lbs
Color	Black
SCC Codes	0073130429140 4
Units per Pallet	24.0

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-9000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

## Conformance

Approvals	CE , GOST
Standard warranty	2 years repair or replace

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs