

Incremental encoders

Solid shaft with clamping or synchro flange, PTB approved

50 or 500 pulses per revolution

GPI0W



GPI0W with clamping flange

Features

- Encoder with solid shaft $\varnothing 10$ mm or $\varnothing 6$ mm
- PTB approved
- Clamping or synchro flange
- High rotation speed max. 10000 rpm
- Compact design
- High resistance to shock and vibrations

Technical data - electrical ratings


| | |
|-----------------------------|-------------------------------|
| Voltage supply | 10...30 VDC |
| Reverse polarity protection | Yes |
| Consumption w/o load | ≤ 30 mA (24 VDC) |
| Pulses per revolution | 50...500 |
| Reference signal | Zero pulse, width 90° |
| Sensing method | Optical |
| Output frequency | ≤ 150 kHz |
| Output signals | A 90° B, 0 |
| Output stage | Push-pull short-circuit proof |
| Interference immunity | DIN EN 61000-6-2 |
| Emitted interference | DIN EN 61000-6-4 |
| Approval | UL approval / E63076 |

Technical data - mechanical design

| | |
|-------------------------|--|
| Size (flange) | $\varnothing 58$ mm |
| Shaft type | $\varnothing 6$ mm solid shaft (synchro flange) $\varnothing 10$ mm solid shaft (clamping flange) |
| Shaft loading | ≤ 20 N axial ≤ 40 N radial |
| Flange | Clamping or synchro flange |
| Protection DIN EN 60529 | IP 54 |
| Operating speed | ≤ 10000 rpm |
| Starting torque | ≤ 0.015 Nm (IP 54) |
| Rotor moment of inertia | 14.5 gcm ² |
| Materials | Housing: aluminium Flange: aluminium |
| Operating temperature | $-25...+85$ °C |
| Relative humidity | 95 % non-condensing |
| Resistance | DIN EN 60068-2-6 Vibration 10 g, 16-2000 Hz DIN EN 60068-2-27 Shock 200 g, 6 ms |
| Connection | Cable 2 m Cable 5 m Cable 10 m |
| Weight approx. | 250 g |

Output signals

Clockwise rotating direction when looking at flange.



Incremental encoders

Solid shaft with clamping or synchro flange, PTB approved

50 or 500 pulses per revolution

GPI0W

Part number

GPI0W. 10

Pulse number - see table

Connection

- 12 Cable 2 m, axial
- 14 Cable 5 m, axial
- 16 Cable 10 m, axial
- 22 Cable 2 m, radial
- 24 Cable 5 m, radial
- 26 Cable 10 m, radial

Voltage supply / signals

- 10 10...30 VDC / push-pull

Flange / Solid shaft

- 0 Clamping flange, mounting M3 / \varnothing 10 mm
- 1 Clamping flange, mounting M4 / \varnothing 10 mm
- 5 Synchro flange, mounting M4 / \varnothing 6 mm

Part number (pulse number)

39 (50) | 15 (500)

Example: part number 15 = 500 pulses.

Accessories

Mounting accessories

| | |
|-----------|---|
| Z 119.006 | Eccentric fixing, single |
| Z 119.013 | Adaptor plate for clamping flange for modification into synchro flange |
| Z 119.015 | Mounting adaptor for synchro flange |
| Z 119.017 | Mounting angle for clamping flange (M3) |
| Z 119.025 | Adaptor plate for clamping flange, mounting by eccentric fixings (order separately) |
| Z 119.035 | Bearing flange for encoders with synchro flange |

Terminal assignment


| Core colour | Assignment |
|-------------|----------------------|
| green | Track N (zero pulse) |
| blue | Track A |
| beige | Track B |
| black | GND (0 V) |
| brown | UB |

Trigger level

| Outputs | Push-pull circuit-proof |
|-------------------|-------------------------|
| Output level High | >UB -3 V (I = -20 mA) |
| Output level Low | <0.5 V (I = 20 mA) |
| Load High | <20 mA |
| Load Low | <20 mA |

Dimensions

Clamping flange



Synchro flange

