CABS Module Kit – CABS3-10T-MOD (549390)












- Modules provide flexibility to select distance between phases and supports
- Installs quickly and easily
- Halogen free insulators
- RoHS compliant



C € EAE ↔

Part Number	CABS3-10T-MOD
Article Number	549390
Material	Steel Glass Fibre Reinforced Polyamide
Finish	Electrogalvanized
Typical Application Current Rating	400 – 4 500 A
Max Working Voltage, IEC (Ui)	1 000 VAC 1 500 VDC
Working Temperature	-40 to 130 °C
Complies With	IEC® 60439.1 IEC® 61439.1 IEC® 60695-2-11 (Glow Wire Test 960 °C)
Flammability Rating	UL® 94V-0
Busbars per Phase	1 – 3
Busbar Width	30 – 120 mm
Busbar Thickness	10 mm
Depth (D)	39 mm
Width (W)	100 mm
Unit Weight	0,45 kg
Certifications	CE EAC 8546901000 (Russian Federation) IEC 61439-1 Busbar Supports RoHS





Part Number	CABS3-10T-MOD
Standard Packaging Quantity	1 рс
UPC	78285668012
EAN-13	3479775493909

CABS modules must be installed on CABS-APP Aluminium Profile.

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



