Optional Products and Maintenance Products

Product name	Specifications	Model	Standards
Memory Cards	Flash memory, 128 MB	HMC-EF183	
	Memory Card Adapter (for computer PCMCIA slot)	HMC-AP001	CE

Product name	Specifications		Model	Standards
Battery Set	Battery for CJ1G/H-CPU□□H-R/H/P CPU Unit maintenance	Note 1.The battery is included as a standard accessory with the CPU Unit. 2. The battery service life is 5 years at 25°C.	CPM2A-BAT01	
	Battery for CJ1M-CPU□□CPU Unit maintenance	 (The service life depends on the ambient operating temperature and the power conditions.) 3. Use batteries within two years of manufacture. 	CJ1W-BAT01	
End Cover	Mounted to the right-hand side of CJ-series CPU Racks or Expansion Racks.	One End Cover is provided as a standard accessory with each CPU Unit and I/O Interface Unit.	CJ1W-TER01	UC1, N, L, CE
RS-422A Adapter	Converts RS-233C to RS-422A/RS-485. (Application example: With a CJ1M CPU Unit, the Adapter is used for Serial PLC Link at the built-in RS-232C port of the CPU Unit.)		CJ1W-CIF11	UC1, N, L, CE

Product name	Specifications		Model	Standards
	Connection configuration	Cable length	Model	Stanuarus
NS-series PT Connecting Cables	Cable for connecting between an NS-series PT and the RS-232C port on the CPU Unit or Serial Communications Board NS-series PT XW2Z-200T (2 m) XW2Z-500T (5 m) RS-232C Cable CPU Unit built-in RS-232C port	2 m	XW2Z-200T	
		5 m	XW2Z-500T	
_	Cable for connecting between an NS-series PT and the peripheral port on	2 m	XW2Z-200T-2	
	the CPU Unit	5 m	XW2Z-500T-2	

DIN Track Accessories

Product name	Specifications	Model	Standards
DIN Track	Length: 0.5 m; Height: 7.3 mm	PFP-50N	
000	Length: 1 m; Height: 7.3 mm	PFP-100N	
	Length: 1 m; Height: 16 mm	PFP-100N2	
End Plate	There are 2 stoppers provided with CPU Units and I/O Interface Units as standard accessories to secure the Units on the DIN Track.	PFP-M	