



EN61326-1
EN61010-1



SPECIFICATIONS

Specifications		UTP3313TFL	UTP3315TFL
Model		CH	CH
Channels		0~30V	0~30V
Output Voltage		0~3A	0~5A
Output Current		$\leq 0.01\%+3mV$	$\leq 0.01\%+3mV$
Load Regulation	Voltage	$\leq 0.2\%+3mA$	$\leq 0.2\%+3mA$
	Current	$\leq 0.01\%+3mV$	$\leq 0.01\%+3mV$
Line Regulation	Voltage	$\leq 0.1\%+3mA$	$\leq 0.1\%+5mA$
	Current	1mVrms	1mVrms
Ripple and Noise	Voltage	3mArms	3mArms
	Current	$\leq \pm 1\%rdg+2digits$	
Display Accuracy		≥ 2000 hours	
Reliability (MTBF)		LED display also shows the voltage and current values	
Display			

GENERAL CHARACTERISTICS

Power	Input Voltage: 115VAC/230VAC(Optional); Frequency: 50Hz/60Hz
Product Colour	White and Gray
Product Net Weight	UTP3313TFL 3.0kg; UTP3315TFL 4.0kg
Product Size (W×H×D)	105mm × 160mm × 230mm
Standard Accessories	Power Cord
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	4 PCs
Standard Carton Measurement(W×H×D)	330mm × 285mm × 460mm
Standard Carton Gross Weight	UTP3313TFL 14.0kg; UTP3315TFL 17.0kg



SPECIFICATIONS

Specifications		UTP3303			UTP3305		
Model		CH1	CH2	CH3	CH1	CH2	CH3
Channels							
Output Voltage		0~32V			0~32V		
Output Current		0~3A			0~5A		
Load Regulation	Voltage	≤0.01%+3mV	≤3%+5mV		≤0.01%+3mV	≤3%+5mV	
	Current	≤0.2%+3mA	--		≤0.2%+3mA	--	
Line Regulation	Voltage	≤0.01%+3mV	5mV		≤0.01%+3mV	5mV	
	Current	≤0.1%+3mA	--		≤0.1%+5mA	--	
Ripple and Noise	Voltage	1mVrms	2mVrms		1mVrms	2mVrms	
	Current	3mA _{rms}	--		3mA _{rms}	--	
Display Accuracy		≤ ±1%rdg+2digits					
Reliability (MTBF)		≥2000 hours					
Display		LED display also shows the voltage and current values					

GENERAL CHARACTERISTICS

Power	Input Voltage: 115VAC/230VAC(Optional); Frequency: 50Hz/60Hz
Product Colour	White and Gray
Product Net Weight	UTP3303- 8.7 kg; UTP3305-10.0 kg
Product Size (W×H×D)	260mm × 176mm × 317mm
Standard Accessories	Power Cord
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	1 PCs
Standard Carton Measurement(W×H×D)	430mm × 400mm × 255mm
Standard Carton Gross Weight	UTP3303- 10 kg; UTP3305-12 kg



EN61326-1
EN61010-1



SPECIFICATIONS

Specifications		Model	UTP1303
Output Voltage		0~32V	
Output Current		0~3A	
Load Regulation	Voltage	$\leq 0.01\% + 3mV$	
	Current	$\leq 0.2\% + 3mA$	
Line Regulation	Voltage	$\leq 0.01\% + 3mV$	
	Current	$\leq 0.1\% + 3mA$	
Ripple and Noise	Voltage	1mVrms	
	Current	3mArms	
Display Accuracy		$\leq \pm 1\%rdg + 2digits$	
Reliability (MTBF)		≥ 2000 hours	
Display		LED display also shows the voltage and current values	

GENERAL CHARACTERISTICS

Power	Input Voltage: 115VAC/230VAC(Optional); Frequency: 50Hz/60Hz
Product Colour	White and Gray
Product Net Weight	5.0 kg
Product Size (W×H×D)	145mm × 175mm × 284mm
Standard Accessories	Power Cord
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	2 PCs
Standard Carton Measurement(L×W×H)	430mm × 400mm × 255mm
Standard Carton Gross Weight	11 kg



EN61326-1
EN61010-1



SPECIFICATIONS

Specifications		UTP1305
Model		UTP1305
Output Voltage		0~32V
Output Current		0~5A
Load Regulation	Voltage	$\leq 0.01\% + 3mV$
	Current	$\leq 0.2\% + 3mA$
Line Regulation	Voltage	$\leq 0.01\% + 3mV$
	Current	$\leq 0.1\% + 5mA$
Ripple and Noise	Voltage	1mVrms
	Current	3mArms
Display Accuracy		$\leq \pm 1\%rdg + 2digits$
Reliability (MTBF)		≥ 2000 hours
Display		LED display also shows the voltage and current values

GENERAL CHARACTERISTICS

Power	Input Voltage: 115VAC/230VAC(Optional); Frequency: 50Hz/60Hz
Product Colour	White and Gray
Product Net Weight	6.0 kg
Product Size (W×H×D)	145mm × 175mm × 284mm
Standard Accessories	Power Cord
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	2 PCs
Standard Carton Measurement(L×W×H)	430mm × 400mm × 255mm
Standard Carton Gross Weight	13 kg