



Model: LP855085		Min.Capacity 最低容量 (mAh) (0.2C,25±3°C) *Single cell capacity (单体电芯容量)	3900	Overcharge Detection Voltage(V) 过充保护电压(V)	4.28±0.05
Battery pack specification (电池组规格)		Typical Capacity 典型容量 (mAh) (0.2C,25±3°C) *Single cell capacity (单体电芯容量)	4100	Overdischarge Detection Voltage(V) 过放电保护电压(V)	3.0±0.1
		Nominal Voltage 标称电压(V)	3.7	Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 3.5 (A)	constant (A) 持续 2.0 (A)
		Internal impedance 内阻(≅) (mΩ,AC 1KHz)	170	Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 (A)	constant (A) 持续 (A)
		Charge Temp. 充电温度(°C)	0~45	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用请识别对PCM的设计至关重要)	
Ambient Conditions (环境温度)		Discharge Temp. 放电温度(°C)	-20~60		
		Humidity(湿度)	65±20%		

Remark(备注): 1. No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象). 2. RoHS compliant(严格按照ROHS要求生产).			
Title	LP855085-PCM-LD	Drawn:	Pengling
File NO.	A06678	Checked 1:	Jane
		Checked 2:	
		Approved:	
		Draw Date:	2012/07/09
		Revision No.:	E4-2009
		Projection:	
		Page:	1/1
		Scale:	1:2
		Unit:	mm