


## LI-M | metric thread

## Connectors

Metal connector, straight, turnable, metric outer thread, integrated ferrule [brass]

**Material:** nickel-plated brass

**Temperature:** -40°C ... +250°C



FLEXA No.	OD [mm]	Threadtype	Conduit ID	Conduit OD	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
5010.012.010	10,0	M 10 x 1,0	7,0	10,0	6,0	17,0	10,0	32,0	15	1,660	50
5010.012.012	14,0	M12 x 1,5	10,0	14,0	9,0	21,0	10,0	33,0	19	2,240	50
5010.012.016	17,0	M16 x 1,5	13,0	17,0	12,0	25,0	10,0	33,0	23	3,200	50
5010.012.020	21,0	M20 x 1,5	17,0	21,0	15,5	29,0	10,0	35,0	27	4,260	50
5010.012.025	27,0	M25 x 1,5	22,0	27,0	20,5	37,0	11,0	36,0	34	7,000	25
5010.012.032	36,0	M32 x 1,5	29,0	36,0	27,5	46,0	13,0	43,0	43	12,080	25
5010.012.040	45,0	M40 x 1,5	38,0	45,0	35,0	62,0	13,0	43,0	54	13,500	25
5010.012.050	56,0	M50 x 1,5	49,0	56,0	45,0	76,0	14,0	44,0	66	25,600	10
5010.712.010	10,0	M 10 x 1,0	7,0	10,0	6,0	16,0	10,0	32,0	15	1,660	10
5010.712.012	14,0	M12 x 1,5	10,0	14,0	9,0	21,0	10,0	33,0	19	2,240	10
5010.712.016	17,0	M16 x 1,5	13,0	17,0	12,0	25,0	10,0	33,0	23	3,200	10
5010.712.020	21,0	M20 x 1,5	17,0	21,0	15,5	29,0	10,0	35,0	27	4,260	10
5010.712.025	27,0	M25 x 1,5	22,0	27,0	20,5	37,0	11,0	36,0	34	7,000	10
5010.712.032	36,0	M32 x 1,5	29,0	36,0	27,5	46,0	13,0	43,0	43	12,080	2
5010.712.040	45,0	M40 x 1,5	38,0	45,0	35,0	62,0	13,0	43,0	54	13,500	2
5010.712.050	56,0	M50 x 1,5	49,0	56,0	45,0	76,0	14,0	44,0	66	25,600	2

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.