

Rittal – The System.

Faster – better – everywhere.

Door-Operated Switch – SZ 4127.210

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Door-Operated Switch – SZ 4127.210

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Function principle: The toggle is actuated via the tubular door frame of the Carbon steel door, or in the case of glazed doors, via an adapter included with the supply.

Product features

Rated operating voltage: 400 V

Installation options: for TS enclosures with installed large swing frame for standard and courtesy lights

For rated current (max.): 240 V AC, 6 A

Rated insulation voltage: 400 V AC

Rated impulse withstand voltage, phase to phase: 6000 V AC

Packaging unit: 1 pc(s).

Weight/packaging unit: 0.26 kg (0.6 lb.)

EAN: 4028177581326

Customs tariff number: 85369095

ETIM 6.0: EC002626

ETIM 5.0:	EC002626
eCl@ss 8.0/8.1:	27189266
eCl@ss 7.0/7.1:	27119116
eCl@ss 6.0/6.1:	27119116
eCl@ss 5.1/5.1.4:	27189241
Product description (long):	SZ Door-operated switch, with toggle, without connection cable, UL
Approvals	
Approvals:	CSA UL
Certificates:	EAC
Declarations:	Declaration of conformity