



**micro selector switch with screw terminals ,SPDT 4 pins LXW2-11**

micro selector switch

1.SPDT 4PIN ON-Momentary ON

2.16A 250VAC

3.screw terminals

- ***The Main Thchnology Performane***

<b>snap action micro switch</b>	
<b>Features:</b>	
5 current ratings	
Choice of actuator styles	
3 terminal types (optional screw terminals available consult factory)	
3 contact arrangements	
Long-life coil spring mechanism	
High-temperature 150°C and 200°C	
available on select models (consult factory)	
<b>Specifications:</b>	
<b>Electrical:</b>	
EllectricalRating:	15A,125/250VAC;3/4HP,125VAC 1-1/2HP,250VAC
Temperature Rating:	105°C Std. (150°C and 200°C optional)
Flammability Rating:	UL94HB
<b>Materials:</b>	
Case:	General Purpose Phenolic
Actuating Button:	Thermoplastic Nylon
Common Terminals:	Brass
NO and NC Terminals:	Brass
Moving Blade:	Brass
Spring:	Stainless Steel
Auxiliary Actuators:	Cold-Rolled Steel (Nickel-Plated)
Roller:	Sintered Stainless Steel
Contacts:	Silver-Cadmium Oxide

- ***Application***

They are widely used in household appliances, electric force, telecommunications, machine tool, vessel, textile, printing, Mining machine, Mustic Instrument, etc.