

High Quality European Manufactured Lubrication Equipment



New specification model!

12851 - Two Hand Grease Gun

Two-hand grease gun, with ergonomic handles for 500g screw-in cartridges. The grease gun is suitable for supplying lubricant greases under pressure up to the viscosity class NLGI 2.

Filling options: 500gm Screw in Cartridge.

Connection: M10x1

Note: Operates with greases up to NLGI grade 2 at 20°C

Max Delivery Pressure: 400 bar

Complete with: M10x1 4-Jaw Precision Coupler and 300mm Flexible High

Pressure Hose.



14601001 - Two Hand easyFILL Grease Gun

Filling options: 400gm Cartridge.

Connection: 1/8BSP

Note: Operates with greases up to NLGI grade 2 at

10°C

Max Delivery Pressure: 400 bar

Complete with: 1/8BSP 4-Jaw Precision Coupler, 300mm Flexible High Pressure Hose and 10

follower plates.



14701002 - One Hand easyFILL Grease Gun

Filling options: 400gm Cartridge.

Connection: 1/8BSP

Note: Operates with greases up to NLGI

grade 2 at 10°C

Max Delivery Pressure: 200 bar (Set on volume)

300 bar (Set on pressure)

Complete with: 1/8BSP 4-Jaw Precision Coupler, 150mm straight rigid pipe and 10 follower plates.



New!

12734804 - Standard Two Hand Grease Gun

Filling options: 400gm Cartridge / Bulk Filling.

Connection: 1/8BSP **Filling Nipple:** M10x1

Note: Operates with greases up to NLGI grade 2

at 20°C

Max Delivery Pressure: 400 bar

Complete with: 1/8BSP 4-Jaw Coupler and

150mm angled rigid pipe.



12675 - Industrial Two Hand Grease Gun

Filling options: 400gm Cartridge / Bulk Filling.

Connection: M10x1 **Filling Nipple:** M10x1

Note: Operates with greases up to NLGI grade 2

at 20°C

Max Delivery Pressure: 400 bar

Complete with: M10x1 4-Jaw Coupler and

150mm angled rigid pipe.



14204212 - Professional Two Hand Grease Gun

Filling options: 400gm Cartridge / Bulk Filling.

Connection: 1/8BSP **Filling Nipple:** M10x1

Note: Operates with greases up to NLGI grade 3

at 20°C

Max Delivery Pressure: 600 bar

Complete with: M10x1 4-Jaw Precision Coupler and 300mm Flexible High Pressure Hose.



12250 - One Hand Grease Gun

Filling options: 400gm Cartridge / Bulk Filling.

Connection: M10x1 **Filling Nipple:** M10x1

Max Delivery Pressure: 200 bar

Complete with: M10x1 4-Jaw Coupler and

150mm straight rigid pipe.



Dublin: 01 4502821 Cork: 021 4354204 Limerick: 061 419158

Manual Barrel Pumps



13012 - Steel Barrel Pump

Delivery Rate approx: 0.3 Litres per stroke / 16 Litres per minute.

Pumping Media: Oils up to SAE90 (Also suitable for Diesel and Petrol)

Usage: 60L / 200L and 220L Containers.

Discharge Spout: Plastic

Length of suction tube: 950mm. **Barrel Screw Coupling:** 2" male.



13055 - Rotary Barrel Pump

Delivery Rate approx: 0.25 Litres per rotation / 25 Litres per minute. **Pumping Media:** Oils up to SAE90 (Also suitable for Diesel and Petrol)

Usage: 60L / 200L and 220L Containers.

Discharge Spout: Steel

Length of suction tube: 980mm. **Barrel Screw Coupling:** 2" male.



Hydraulic Grease Nipples







Description	Straight Grease Nipple Part #	45° Grease Nipple Part #	90° Grease Nipple Part #
Grease Nipple 1/8BSP	15037	15137	15237
Grease Nipple 1/4BSP	15038	15138	15238
Grease Nipple 1/4BSF	15000	15100	15200
Grease Nipple 5/16BSF	15069		
Grease Nipple 1/4UNF	15062	15162	
Grease Nipple M6x1	15007	15107	15207
Grease Nipple M8x1	15009	15109	15209
Grease Nipple M8x1.25	15010	15110	15210
Grease Nipple M10x1	15013	15113	15213
Grease Nipple M10x1.25	15014	15114	15214
Grease Nipple M10x1.5	15015	15115	15215

16090 - 140 Piece Assorted Grease Nipple Set

M6x1 (25 pieces straight, 10 pieces 45° , 10 pieces 90°)

M8x1 (25 pieces straight, 10 pieces 45° , 10 pieces 90°)

M10x1 (15 pieces straight, 5 pieces 45⁰, 5 pieces 90⁰)

1/8BSP (15 pieces straight, 5 pieces 45° , 5 pieces 90°)



Ancillary Parts



- Heavy duty precision coupler, suits all grease gun types
- Maintains a leak free HOLD even at extreme pressure
- Suitable for all commercially available hydraulic grease nipples (DIN & SAE specification)
- Detachable at high pressure
- Hands Free to operate grease gun
- Low wear long service life
- Ease of removal detatchesd simply by tilting laterally 30° from grease nipple

12643 - Precision Coupler 4-Jaw Turned.

For Grease Nipples: Standard H1

Grease Hose /Pipe Connection: M10x1

Material: Galvanised Steel.

12743 - Precision Coupler 4-Jaw Turned.

For Grease Nipples: Standard H1 Grease Hose /Pipe Connection: 1/8BSP

Material: Galvanised Steel.





12731 - Hydraulic Coupler 4-Jaw Punched.

For Grease Nipples: Standard H1 **Grease Hose /Pipe Connection:** 1/8BSP

Material: Galvanised Steel.



12631 - Hydraulic Coupler 4-Jaw Punched.

For Grease Nipples: Standard H1 Grease Hose /Pipe Connection: M10x1

Material: Galvanised Steel.



12061 - Button Head Coupler - Slide on type

For Grease Nipples: Head Ø 16mm **Grease Hose /Pipe Connection:** M10x1

Material: Brass.



12062 - Button Head Coupler - Slide on type

For Grease Nipples: Head Ø 16mm Grease Hose /Pipe Connection: M10x1

Material: Brass.



12063 - Button Head Coupler - Slide on type

For Grease Nipples: M22, Head Ø 22mm Grease Hose /Pipe Connection: M10x1

Material: Brass.



12670 - Pressol Bulk Filling Nipple for Grease Gun

Head

Connection grease gun side: M10x1 Connection filling side: Outside Ø 9mm



12756 - High Pressure Flexible Hose - Polyamide **Outer**

Connection both ends: 1/8BSP

Length: 300mm.

Burst Pressure: 900 bar

12766 - High Pressure Flexible Hose - Polyamide Outer

Connection both ends: 1/8BSP

Length: 500mm. Burst Pressure: 900 bar

12655 - High Pressure Flexible Hose -

Polyurethane Outer

Connection both ends: M10x1

Length: 300mm. Burst Pressure: 900 bar

12765 - High Pressure Flexible Hose -

Polyurethane Outer

Connection both ends: 1/8BSP

Length: 500mm. Burst Pressure: 900 bar

12735 - Galvanised Steel Rigid Pipe

Connection both ends: 1/8BSP Length: 150mm.

