



FEIN SuperCut FSC 2.0 X Joint Restoration

Oscillating multi-tool - 400 W

The highest performance system for interior construction and renovation, with special accessories for the most common applications in caulking/ sealant repair.

Product number: 7 236 38 61 09 0

Details

- > Hexagonal tool mount for outstanding torque transfer between tool and accessories.
- > Highest quality and stability due to the use of ball and needle bearings together with a motor and gearbox designed for continuous use and heavy loads.
- > Ergonomic design for fatigue-free work.
- > Vibration-absorbing bail handle to minimize physical strain.
- > Dust extraction assembly attaches without tools.

Price includes

- ✓ 1 elongated pointed blade (type 116)
- ✓ 1 vibration-reducing handle
- ✓ 5 cutter blades, straight (type 117)
- ✓ 1 tool case



Technical data

TECHNICAL DATA

Power consumption	400 W
Power output	220 W
Oscillations	11,000 - 18,500 opm
Tool mount	Hexagon
Tool change	Manual with screw, hexagonal socket
Range	2 x 2,0°
Cable with plug	16.4 [5] ft[m]
Weight according to EPTA	2.76 [1.25] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	79 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	90 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	93 dB 3 dB

Application examples

