


UT-085

50 OHM SEMI-RIGID CABLES



Copper 50 ohm semi-rigid cables feature low attenuation and VSWR covering the entire microwave spectrum. With numerous connector options available off-the-shelf, this family of cables is one of the most versatile available today. They meet the demands of package density and provide total shielding for elimination of signal loss and noise.



DIMENSIONS

	UNITS	UT-085
Outer Conductor Diameter	In	0.0865 ± 0.0010
	mm	2.1971 ± 0.0254
Center Conductor Diameter	In	0.0201
	mm	0.5105
length (maximum)	Feet	20
	Meter	6.10

MATERIALS

Outer Conductor		Copper
Outer Conductor Plating		None
Dielectric		PTFE
Center Conductor		SPCW
Rohs Compliant		YES

MECHANICAL CHARACTERISTICS*

Outer Conductor Integrity Temp.	°C	175
Operating Temperature (Max)	°C	125
Inside Bend Radius (Minimum)	In	0.050
	mm	1.270
Weight	lbs / 100ft	1.42
	kg / 100m	2.13

ELECTRICAL CHARACTERISTICS*

Characteristic Impedance	ohm	50
Capacitance	pF/ ft	29.0
	pF/ m	95.2
Corona Extinction Voltage	VRMS @ 60 Hz	1500
Voltage Withstanding	VRMS @ 60 Hz	5400
Higher Order Mode Frequency	GHz	61.0
Attenuation (Db / 100 Ft Typical)	0.5 GHz	13.6
	1.0 GHz	19.5
	5.0 GHz	46
	10.0 GHz	67.4
	18.0 GHz	94.3
	26.5 GHz	118.3
	40.0 GHz	151.5
	50.0 GHz	173.8
	65.0 GHz	N/A
Power (Watts Cw @ 20 °C, Maximum)	0.5 GHz	232
	1.0 GHz	162.5
	5.0 GHz	69.8
	10.0 GHz	47.9
	18.0 GHz	34.6
	26.5 GHz	27.7
	40.0 GHz	21.8
	50.0 GHz	19.1
	65.0 GHz	N/A
90.0 GHz	N/A	

* Applicable at room temperature. Contact factory for performance over temperature range.

CHECK OUT OTHER RELATED PRODUCTS

» **UTiFLEX Flexible Cable Assemblies**
<https://www.carlisleit.com/products/branded-technologies/utiflex>

» **RF/Microwave Products**
<https://www.carlisleit.com/products/rf-products>

CONNECT WITH US TODAY

www.CarlisleIT.com

+1 (610) 495-0110
rfcables@CarlisleIT.com