

Completely pre-assembled Signal Towers / deSIGN 42

Signal tower deSIGN42 EM 24VDC GN/RD



| MECHANICAL DATA | |
|-----------------------------|-----------------------|
| Height | 206 mm |
| Diameter | 42 mm |
| Materials | PC Stainless steel |
| Cap colour | Clear |
| Housing colour | Silver |
| Protection category | IP65 |
| Connection | Cable |
| Cable length | 2000 mm |
| Type of fixing | Built-in mounting |
| Service life optical | 50,000 h maximum |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Total weight in g | 792 g |
| Net weight in g | 715 g |

| ELECTRICAL DATA | |
|---------------------------|--------|
| Voltage | 24V |
| voltage type | DC |
| Total current consumption | 50 mA |
| Starting current | 500 mA |

| OPTICAL DATA | |
|----------------------|--------------|
| Light source | LED |
| Light colour | Green Red |
| Optical signal image | Duration |

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.



Completely pre-assembled Signal Towers / deSIGN 42

Signal tower deSIGN42 EM 24VDC GN/RD

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.