

# HUBER+SUHNER® DATA SHEET

## Between Series Adapter: 33\_BNC-MCX-50-1/1--\_U

Rev.: B



### Description

Adaptor plug/jack  
BNC plug (male) / MCX jack (female)

Interface standards  
IEC 60169-8\_MIL-STD-348A/301\_CECC 22120



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
Frequency range	DC to 4 GHz
Return loss	≥ 21 dB

#### Mechanical Data

Number of matings	500
Weight	0.0117 kg

#### Environmental Data

Operating Temperature	-55 °C to 155 °C
2002/95/EC (RoHS)	compliant

#### Material Data

##### Piece Parts (BNC)

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Coupling nut	Brass
Gasket	MVQ (Silicone Rubber)

##### Piece Parts (MCX)

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE

##### Surface Plating

Gold Plating  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

##### Surface Plating

Gold Plating  
Gold Plating  
Gold Plating

### Related Documents

Catalogue drawing	DCA-00014395
-------------------	--------------

### Ordering Information

Single package	33_BNC-MCX-50-1/1--_UE
----------------	------------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**