

U.I. Lapp GmbH	PRODUCT INFORMATION	
	SKINTOP® GMP-HF-M	07.11.2014

Halogen-free
 Extremely flame-retardant according to UL 94 V0
 Self-extinguishing, no dripping



Halogen-free



Assembly time



Temperature-resistant



Variety of approval certifications

Info

Cable gland for railway applications- Fire protection on railway vehicles Approval according to DIN EN 45545-2:2013

Application range

For locking SKINTOP® cable glands in boreholes without thread.

Airports

Tunnel construction

Underground railways

Public buildings

Product Make-up

Metric connection thread acc. to EN 50262

Note

Designed for use with SKINTOP® ST-HF-M

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: cable screw gland
Colour delivered:	Light grey (RAL 7035)
Material:	Polyamide UL 94V-0 - halogen-free
Temperature range:	-20°C to +100°C

Product Management	Document: LAPP_PRO26780EN.pdf	1 / 2
--------------------	-------------------------------	-------

SKINTOP® GMP-HF-M

07.11.2014

Part number	Article designation / size	SW (mm)	PU
SKINTOP® GMP-HF-M			
53119200	12 x 1,5	17	100
53119210	16 x 1,5	22	100
53119220	20 x 1,5	27	100
53119230	25 x 1,5	34	100
53119240	32 x 1,5	41	100
53119250	40 x 1,5	50	25
53119260	50 x 1,5	60	25
53119270	63 x 1,5	75	25