



| Code | Icon | D | L mm | W mm | P mm | Q |
|---------|------|------|------|--------|------|-----|
| BE-8904 | T 4 | 1,30 | 75 | 20x122 | 5 | 30 |
| BE-8905 | T 5 | 1,37 | 75 | 20x122 | 5 | 30 |
| BE-8906 | T 6 | 1,65 | 75 | 20x122 | 5 | 30 |
| BE-8907 | T 7 | 1,97 | 75 | 20x122 | 5 | 30 |
| BE-8908 | T 8 | 2,30 | 75 | 20x122 | 5 | 32 |
| BE-8909 | T 9 | 2,48 | 75 | 20x122 | 5 | 33 |
| BE-8910 | T 10 | 2,72 | 75 | 20x122 | 5 | 31 |
| BE-8915 | T 15 | 3,26 | 100 | 27x122 | 5 | 57 |
| BE-8920 | T 20 | 3,84 | 100 | 27x122 | 5 | 57 |
| BE-8925 | T 25 | 4,40 | 125 | 27x122 | 5 | 70 |
| BE-8927 | T 27 | 4,96 | 125 | 27x122 | 5 | 70 |
| BE-8930 | T30 | 5,49 | 150 | 36x122 | 5 | 119 |

Double handle



| Code | Icon | D | L mm | W mm | P mm | Q |
|---------|------|------|------|--------|------|-----|
| BE-8940 | T40 | 6,60 | 150 | 36x165 | 5 | 130 |
| BE-8945 | T45 | 7,70 | 150 | 36x165 | 5 | 178 |

Torx® Tamper



| Code | Icon | D | L mm | W mm | P mm | Q |
|---------|-------|------|------|--------|------|-----|
| BE-7907 | TR 7 | 1,97 | 75 | 20x122 | 5 | 31 |
| BE-7908 | TR 8 | 2,30 | 75 | 20x122 | 5 | 31 |
| BE-7909 | TR 9 | 2,48 | 75 | 20x122 | 5 | 31 |
| BE-7910 | TR 10 | 2,72 | 75 | 20x122 | 5 | 31 |
| BE-7915 | TR 15 | 3,26 | 100 | 27x122 | 5 | 57 |
| BE-7920 | TR 20 | 3,84 | 100 | 27x122 | 5 | 57 |
| BE-7925 | TR 25 | 4,40 | 125 | 27x122 | 5 | 70 |
| BE-7927 | TR 27 | 4,96 | 125 | 27x122 | 5 | 70 |
| BE-7930 | TR 30 | 5,49 | 150 | 36x122 | 5 | 119 |

Torx® Tamper double handle



| Code | Icon | D | L mm | W mm | P mm | Q |
|---------|-------|------|------|--------|------|-----|
| BE-7940 | TR 40 | 6,60 | 150 | 36x165 | 5 | 130 |

TORX® TAMPER

Torx®, Tamper-Resistant contains a post or pin in the center of the head that prevents a «standard» Torx® driver from being inserted which means safety screws cannot be unscrewed.



Torx® Ball



| Code | Icon | D | L mm | W mm | P mm | Q |
|---------|------|------|------|--------|------|-----|
| BE-7515 | T 15 | 3,26 | 100 | 27x122 | 5 | 57 |
| BE-7520 | T 20 | 3,84 | 100 | 27x100 | 5 | 57 |
| BE-7525 | T 25 | 4,40 | 125 | 27x122 | 5 | 70 |
| BE-7527 | T 27 | 4,96 | 125 | 27x122 | 5 | 70 |
| BE-7530 | T 30 | 5,49 | 150 | 36x122 | 5 | 119 |
| BE-7540 | T 40 | 6,60 | 150 | 36x122 | 5 | 119 |

TORX® BALL

The spherical drive profile allows work at an angle of up to 30° with total effectiveness. TORX® BALL end tips are necessary when screwdriving in tight spots or at an angle.




Torx Plus®



| Code | Icon | D | L mm | W mm | P mm | Q |
|---------|------|------|------|--------|------|-----|
| BE-7715 | T 15 | 3,26 | 100 | 27x122 | 5 | 57 |
| BE-7720 | T 20 | 3,84 | 100 | 27x100 | 5 | 57 |
| BE-7725 | T 25 | 4,40 | 125 | 27x122 | 5 | 70 |
| BE-7727 | T 27 | 4,96 | 125 | 27x122 | 5 | 70 |
| BE-7730 | T 30 | 5,49 | 150 | 36x122 | 5 | 119 |
| BE-7740 | T 40 | 6,60 | 150 | 36x122 | 5 | 119 |

TORX PLUS®

TORX PLUS® is designed to allow greater torque, to minimize wear and to increase productivity by reducing down-time. With a larger contact area than the standard Torx®, the amount of transmission increases, as well as the life time of the tools.



TORX® vs. TORX PLUS®

