

Rhino™ 4200



Compact, Time-Saving Label Maker for On-The-Go Pros

- Familiar computer-style keyboard with country-specific layout for fast and easy text entry
- One-Touch “Hot Keys” provide shortcuts for creating and formatting wire/cable wraps, flags, Code 39 and Code 128 bar codes, fixed-length, general and breaker labels
- “Favorites” key provides single-key access to your most commonly used labels, symbols and terms
- Avoid repeated steps with the “Custom” key – customize and save settings for individual label formats
- Pre-programmed library with 150 symbols and terms for security, electrical, pro A/V, and facilities management
- Integrated rubber bumpers help prevent damage from accidental drops and falls
- Large back-lit display is easy to read, even in dimly-lit work areas
- Prints 57% faster than the competition*

*Based on independent testing of Rhino 4200 vs. Brother PT-1400 and Brother PT-7100 in default settings



Single Unit Includes:

- Rhino 4200 Label Maker
- 12 mm White Vinyl Label Cartridge
- Quick Reference Guide



Quick Specs

| | |
|-----------------------------|-------------------------------------|
| Unit Dimensions (H x W x L) | 215 x 103 x 57 mm |
| Weight (excluding battery) | 540 g |
| Mac®/PC Compatible | No |
| Accepts Label Sizes | 6mm, 9mm, 12mm, 19mm |
| Tape Platform | IND Rhino™ |
| Resolution | 180 dpi |
| Printing System | Thermal Transfer |
| Print Speed | 15mm/sec |
| Barcodes | Yes, Code 39 & Code 128 |
| Cutter Type | Manual |
| Batteries | 6 AA or Rechargeable (not included) |
| AC Adapter | Yes (not included) |
| Networking | No |
| Country of Origin | China |

| Item Number | Description | | Length (cm) | Width (cm) | Height (cm) | Weight (kg) | QTY | EAN | Customer Price |
|--------------------|----------------------|--------|-------------|------------|-------------|-------------|-----|----------------|----------------|
| S0955950 | RHINO 4200 UK/IRL | Unit | 8.8 | 15.6 | 23.0 | 0.7 | 1 | 3501170955956 | |
| | | Shelf | - | - | - | - | - | - | - |
| | | Case | 23.0 | 20.0 | 35.0 | 3.2 | 4 | 13501170955953 | |
| | | Pallet | 120.0 | 80.0 | 120.0 | 216.3 | 240 | - | |
| Accessories | | | | | | | | | |
| S0721430 | RHINO AC Adapter | Unit | 11.5 | 5.9 | 8.9 | 0.2 | 1 | 5411313400756 | |
| S0895840 | Rechargeable battery | Unit | 8.5 | 3.2 | 8.9 | 0.1 | 1 | 3501170895849 | |



IND Vinyl

Ideal for both indoor and outdoor applications. Available in the widest range of colors that meet OSHA, ANSI and ISO color standards.

- UL recognized component to UL 969
- RoHS compliant
- Temperature rating: -40°C to 80°C

IND Flexible Nylon

Specifically designed for curved surfaces and wire and cable marking.

- UL recognized component to UL 969
- RoHS compliant
- Temperature rating: -10°C to 80°C

IND Permanent Polyester

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins, beams and more.

- UL recognized component to UL 969
- RoHS compliant
- For flat surfaces only
- Temperature rating: -40°C to 150°C

IND Heat-Shrink Tube

For high-end cable identification. A 3:1 shrink ratio helps ensure a secure fit on wires and cables.

- Meets MIL-M-81531, MIL-STD-202G, SAE-DTL-23053/5 (Class 1 & 3)
- UL recognized as a component to UL 224
- RoHS compliant
- Temperature rating: -55° C to 135°C

| IND Compatible Labels | | | | | | | | | | | | |
|--------------------------------|--------|---------|----------|-------|-------|---------|---------|---------|---------|---------|---------|---------|
| Width | Length | A | A | A | A | A | A | A | A | A | A | A |
| IND VINYL | | | | | | | | | | | | |
| 9mm | 5.5m | 18443 | - | - | - | - | - | 1805437 | - | - | - | - |
| 12mm | | 18444 | - | 18432 | 18435 | 1805413 | 1805416 | 1805435 | 1805414 | 1805243 | 1805415 | 1805412 |
| 19mm | | 18445 | - | 18433 | 18436 | 1805419 | 1805422 | 1805436 | 1805420 | 1805417 | 1805421 | 1805418 |
| IND PERMANENT POLYESTER | | | | | | | | | | | | |
| 6mm | 5.5m | 1805442 | 1805440 | - | - | 1805441 | - | - | - | - | - | - |
| 9mm | | 18482 | 18508DMO | - | - | 18485 | - | - | - | - | - | - |
| 12mm | | 18483 | 622289 | - | - | 18486 | - | - | - | - | - | - |
| 19mm | | 18484 | 622290 | - | - | 18487 | - | - | - | - | - | - |
| IND FLEXIBLE NYLON | | | | | | | | | | | | |
| 12mm | 3.5m | 18488 | - | 18490 | - | - | - | - | - | - | - | - |
| 19mm | 3.5m | 18489 | - | 18491 | - | - | - | - | - | - | - | - |
| IND HEAT-SHRINK TUBE | | | | | | | | | | | | |
| 6mm | 1.5m | 18051 | - | 18052 | - | - | - | - | - | - | - | - |
| 9mm | | 18053 | - | 18054 | - | - | - | - | - | - | - | - |
| 12mm | | 18055 | - | 18056 | - | - | - | - | - | - | - | - |
| 19mm | | 18057 | - | 18058 | - | - | - | - | - | - | - | - |

Country of Origin: Belgium

DISTRIBUTED BY:
 Newell Europe Sàrl
 Chemin de Blandonnet 10
 1214 Vernier – Switzerland
 WWW.DYMO.COM



A NewellRubbermaid Company™

SCHAWK!

RMZ Millennia Business Park
Campus - 2, 5th Floor
No. 143, Dr.M. G. R. Road
Kandanchavadi | Chennai 600 098 India
T +91 44 4213 7777 | www.schawk.com



Use the PANTONE MATCHING SYSTEM for accurate color reproduction

| | | |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| VERSION | JOB DESCRIPTION : NRM_EU_Writing_Dymo_1362812_EMEA Product Handbooks_UK Masters FILE NAME : DY_1362812_2014_EMEA_RH4200_TecSheet_v5.indd | BRAND : WRITING-DYMO |
| 5 Date: 10-10-2014 Operator : HL | SCHAWK JOB # : 3102530 NRM JOB # : 1362812 SAP / FG # : N/A COMPONENT # : N/A NO OF PAGES : 2 | DIELINE : XXXXX UPC : XXXXX VENDOR : XXXXX |

Note :