




SPECIFICATION

ITEM	SPS-150	
OUTPUT POWER	CONTINUOUS POWER 150W	SURGE POWER 450W
STANDBY CURRENT	DC 12V < 0.3A	DC 24V < 0.2A
INPUT VOLTAGE	DC12V : 10V~15V	DC24V : 20V~30V
OUTPUT VOLTAGE	AC 100V, 110V, 120V, 220V, 230V, 240V	
OUTPUT WAVEFORM	Modified Sine Wave	
EFFICIENCY	>90%	
※ INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V	
※ OUTPUT REGULATION	± 5% INTELLIGENT AVR	
※ OUTPUT FREQUENCY	50Hz , 55Hz , 60Hz CRYSTAL CONTROLLED.	
※ COOLING	BY AIR CONVECTION	
※ OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION	
※ LOW BATTERY	< 11V or 22V ± 0.5V/1V PRE-ALARM	< 9.5V or 20V ± 0.5V/1V SHUT DOWN & ALARM
※ OVER HEATING	> 60°C PRE-ALARM	> 65°C SHUT DOWN & ALARM
※ OVER LOAD	> 150W PRE-ALARM	> 160W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE	
FUSE	DC 12V : 15A * 1PCS	DC 24V : 10A * 1PCS
AC OUTLET	1 AC OUTLET	
DIMENSION (L*W*H)	(U) 100*73*45mm	(E) 100*73*73mm
NET WEIGHT	(U) 0.36Kg	(E) 0.46Kg

※ MARK ARE OUR UNIQUE FUNCTIONS