



## VINYL-INSULATED (EASY ENTRY) SPADE TERMINALS

**MAXIMUM ELECTRIC CURRENT:**

A.W.G.	22	20	18	16	14	12	10
AMP.	9	12	17	18	30	35	50

**MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.**

**INSULATION MATERIAL: VINYL**

**INSULATION COLOR:**

22-16A.W.G.: RED ■ 16-14A.W.G.: BLUE ■

12-10A.W.G.: YELLOW ■

**TERMINAL MATERIAL: COPPER**

WIRE RANGE A.W.G. mm <sup>2</sup>	ITEM NO.		STUD SIZE	DIMENSION inch(mm)								Q'TY BOX
	BRAZED SEAM	BUTTED SEAM		d2	W	F	L	E	D	d1	T	
12-10 A.W.G. 4-6 mm <sup>2</sup>	SVEBSS-3.7	SVES5-3.7	#6	0.146 3.7	0.283 7.2	0.295 7.5	1.004 25.5	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	SVEB5-3.7	SVE5-3.7	#6	0.146 3.7	0.327 8.3	0.276 7	1.047 26.6	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	SVEBSS-4	SVES5-4	#8	0.169 4.3	0.283 7.2	0.295 7.5	1.004 25.5	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	SVEB5-4	SVE5-4	#8	0.169 4.3	0.327 8.3	0.276 7	1.047 26.6	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	SVEBL5-4	SVEL5-4	#8	0.169 4.3	0.354 9	0.276 7	1.047 26.6	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	SVEB5-5	SVE5-5	#10	0.209 5.3	0.354 9	0.276 7	1.047 26.6	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	SVEBSS-6	SVES5-6	1/4	0.252 6.4	0.354 9	0.276 7	1.047 26.6	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	SVEBL5-6	SVEL5-6	1/4	0.252 6.4	0.472 12	0.472 12	1.283 32.6	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500
	SVEB5-8	SVE5-8	5/16	0.331 8.4	0.551 14	0.413 10.5	1.244 31.6	0.555 14.1	0.248 6.300	0.134 3.4	0.039 1	500

