

DIN-rail time switches

Features

- Autom. summertime / wintertime changeover: automatic / free selectable / OFF
- 12/24h time setting
- Switching state display
- Sealable
- Non-volatile memory (EEPROM)

Applications

- Advertising signs
- Street lighting
- Shop window lighting
- Home & work environment
- Devices, motors and pumps control

Voltage	EAN-Code 4010940	Ord.-No.	Languages operating manual
---------	------------------	----------	----------------------------



talento 371 mini plus (1 channel)

230 V / 50-60 Hz	034078	03.72.0001.1	
------------------	--------	--------------	--

- 50 Memory spaces
- Weekly program (ON/OFF)
- Holiday program (ON/OFF)
- Shortest switching time: 1 min.
- Manual switch: fix ON/OFF



talento 371 pro (1 channel)

110-230 V AC	041953	03.96.0002.1	DE, EN, FR, IT, CS, HU
110-230 V AC	042349	03.96.0006.1	ES, PT, NL, PL, NO, SV, DA, FI

talento 372 pro (2 channels)

110-230 V AC	041960	03.96.0003.1	DE, EN, FR, IT, CS, HU
110-230 V AC	042356	03.96.0007.1	ES, PT, NL, PL, NO, SV, DA, FI

talento 371 pro, talento 372 pro

- 70 Memory spaces
- Backlight
- PIN-Code
- Hour counter with service function
- Weekly program (ON/OFF)
- Holiday program (ON/OFF, OFF)
- Shortest switching time: 1 min.
- Free weekday block formation
- Manual switch: Automatic / Override / fix ON/OFF



talento 751 pro (1 channel)

110-230 V AC	041977	03.96.0004.1	DE, EN, FR, IT, CS, HU
110-230 V AC	042363	03.96.0008.1	ES, PT, NL, PL, NO, SV, DA, FI

talento 752 pro (2 channels)

110-230 V AC	041984	03.96.0005.1	DE, EN, FR, IT, CS, HU
110-230 V AC	042370	03.96.0009.1	ES, PT, NL, PL, NO, SV, DA, FI

talento 751 pro, talento 752 pro

- 70 Memory spaces
- Backlight
- PIN-Code
- Hour counter with service function
- Holiday program (ON/OFF, OFF)
- Astro program
- Shortest switching time: 1 min.
- Free weekday block formation
- Manual switch: Automatic / Override / fix ON/OFF

Technical data

	talento 371 mini plus	talento 371/372 pro	talento 751/752 pro
Dimensions H x W x D (mm)	45 x 17,5 x 60	45 x 35 x 60	
Width	1 module	2 modules	
Distributor cut-out (mm)	46 x 18	46 x 36	
Installation type	DIN-rail	DIN-rail	
Weight (g) approx.	100	170	
Connection voltage	230 V / 50-60 Hz	110 - 230 V AC / 50-60 Hz	
Power consumption at 230 V~ (AC)	5 VA	1 VA	
Switch contacts	1 CO	1 CO	1 CO + 1 NO
Switching output	phase-independent	phase-independent (zero cross switching)	
Opening width	< 3 mm	< 3 mm	
Lamp type			
– Resistive	16 A / 250 V AC	16 A / 250 V, cos φ = 1	
– Inductive	8 A / 250 V AC	10 A / 250 V, cos φ = 0,6	
– Incandescent	1000 W	2600 W	
– Fluorescent			
Uncorrected	–	1000 VA	
Serial corrected	–	1000 VA	
Parallel corrected	–	730 VA (80 μF)	
Lead-lag (duo)	–	1000 VA	
– Halogen lamp load	–	2600 W	
– Compact fluorescent lamp	–	22x7 W, 18x11 W, 16x15 W, 16x20 W, 14x23 W	
– Energy saving lamps 230 V	–	37x7 W, 30x11 W, 26x15 W, 26x20 W, 11x23 W	
Rated load AC1/AC15	–	4000 VA / 750 VA	
Min. switching load	–	300 mW	
DC Switching capacity (24V-/50V-/220V-)	800 mA / 300 mA / 150 mA	800 mA / 300 mA / 150 mA	
Housing and insulation material	high-temperature resistant, self-extinguishing thermoplastic	high-temperature resistant, self-extinguishing thermoplastic	
Ambient temperature	-10°C ... +55°C	-25°C* ... +55°C	
Protection class (EN60730-1)	II	II	
Type of protection (EN60529)	IP 20	IP 20	
Accuracy	Typ ± 1 sec./day at +20°C	Typ ± 0,5 sec./day at +20°C	
Time basis	quartz	quartz	
Power reserve	3 years ex works at +20°C (Replaceable battery CR2032)	3 years ex works at +20°C (Replaceable battery CR2032)	
Max. terminal capacity	2,5 mm ²	1 - 4 mm ²	
Connection type	Captive ± screw terminal	Captive ± screw terminal	
Battery type	CR2032	CR2032	

Accessories		
Assembly accessories	see page 28	see page 28

* Limited display readability possible, however full functionality guaranteed.

Dimensional drawings / circuit diagrams:

