



Low-Heat Shrinkable Tubing 2:1

- TCN20 - self extinguishing

TCN20 is suitable for a wide range of applications such as electrical insulation, mechanical protection and cable bundling.

Features and Benefits

- Thin walled general purpose polyolefin tubing
- Highly flame-retardant, UL224 VW-1 , CSA
- Fast shrinking
- Low shrink temperature



Heat Shrink Tubing TCN20.

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	2:1
Operating Temperature	-55 °C to +125 °C
Minimum Shrink Temperature	+100 °C
Longitudinal change after shrinkage	+/-5%
Dielectric Strength	20kV/mm according to ASTM D2671
Flammability	Self extinguishing
Specifications	CSA, UL224 125 °C 600V VW-1



Heat Shrinkable Tubing 2:1

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
TCN20-1.2/0.6	1.2	0.6	0.30	300 m	Black (BK)	300-73010
TCN20-1.6/0.8	1.6	0.8	0.35	300 m	Black (BK)	300-73020
TCN20-2.4/1.2	2.4	1.2	0.45	300 m	Black (BK)	300-73030
TCN20-3.2/1.6	3.2	1.6	0.45	300 m	Black (BK)	300-73040
TCN20-4.8/2.4	4.8	2.4	0.50	300 m	Black (BK)	300-73050
TCN20-6.4/3.2	6.4	3.2	0.55	300 m	Black (BK)	300-73060
TCN20-9.5/4.8	9.5	4.8	0.55	100 m	Black (BK)	300-73070
TCN20-12.7/6.4	12.7	6.4	0.65	100 m	Black (BK)	300-73080
TCN20-19.1/9.5	19.1	9.5	0.80	60 m	Black (BK)	300-73090
TCN20-25.4/12.7	25.4	12.7	0.90	60 m	Black (BK)	300-73100
TCN20-38.1/19.1	38.1	19.1	1.02	30 m	Black (BK)	300-73110
TCN20-50.8/25.4	50.8	25.4	1.15	30 m	Black (BK)	300-73120

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval.
For product specific approvals please refer to the Appendix.