

Bits for TORX PLUS® Screws



EAN:	4013288113238	Size:	60x6x5 mm
Part number:	05135442001	Weight:	7 g
Article number:	867/22 TORX PLUS®	Country of origin:	CZ
		Customs tariff number:	82079030

- For TORX PLUS® screws
- Ductile and tough for hard materials
- HIOS drive 5 mm
- Suitable for CL-6000, CL-6500, CL-7000, SS-6500, SS-7000, L-6500 etc.
- Prevents premature breakage of the drive tip

High quality bits for recessed TORX PLUS® screws. Tough viscous for universal use. Drive: HIOS 5 mm.

Web link

https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_torx_plus_screws_867_22_torx_plus.html

Wera - 867/22 TORX PLUS®
05135442001 - 4013288113238

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Bits for TORX PLUS® Screws

TORX PLUS®

5 mm HIOS direct drive



Compared with the "normal" TORX® profile, the elliptical instead of circular profile enlarges the 6 flanks that transfer torque between the tool and the screw. This means that the force applied when screwdriving is spread across a larger surface area. Higher torque is transferred and, in addition, the service life of the screw and tool are lengthened. The so-called centre-lock screws on cutting tools represent a typical use of this type of screw profile. The thermal influences on such holders for carbide insert tips often "bake" the retaining screws so firmly that it is important to have a profile that considerably enhances the loosening torque capability of the screws. For this reason a torque-stable screw profile is necessary to avoid any possible damage to the screw and to exclude the possibility of an otherwise costly machine downtime.

HIOS, 5mm, Wera Series 22. Drive: For direct machine drive. Suitable for: CL-6000, CL-6500, CL-7000, SS-6500, SS-7000, L-6500, CD-6000, CD-7000, VZ-1820 (100 V), VZ-3012 (100 V) (incl. PS-Typ).

Web link







https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_torx_plus_screws_867_22_torx_plus.html

Wera - 867/22 TORX PLUS®
05135442001 - 4013288113238

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Bits for TORX PLUS® Screws

Further versions in this product family:

						
		mm	inch	mm	mm	inch
05135440001	5 IP	60	2 3/8	2.0	20	25/32
05344280001	6 IP	60	2 3/8	2.5	20	25/32
05135441001	7 IP	60	2 3/8	2.5	20	25/32
05134500001	8 IP	60	2 3/8	3.0	20	25/32
05344281001	8 IP	80	3 1/8	3.0	20	25/32
05135442001	9 IP	60	2 3/8	3.0	20	25/32
05135443001	10 IP	60	2 3/8	3.0	20	25/32
05344282001	10 IP	80	3 1/8	3.0	20	25/32

Web link

https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_torx_plus_screws_867_22_torx_plus.html

Wera - 867/22 TORX PLUS®
05135442001 - 4013288113238

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de