



ATEX
II 2G 1D



Material
O-Ring
Protection

Stainless steel (1.4305)
Buna-N/VQM
IP 68 – 10 bar / IP 69K

EEx e II DMT 03 ATEX E 049

For approvals see page 162



AG	IG	GL mm	H mm	Buna-N		VQM	
				20°C – 95°C (-4°F – 208°F)	-60°C – 180°C (-76°F – 356°F)	20°C – 95°C (-4°F – 208°F)	-60°C – 180°C (-76°F – 356°F)
M 16 x 1,5	M 12 x 1,5	5	17	1.098.1612.50	1.099.1612.50		
M 20 x 1,5	M 12 x 1,5	6	22	1.098.2012.50	1.099.2012.50		
M 20 x 1,5	M 16 x 1,5	6	22	1.098.2016.50	1.099.2016.50		
M 25 x 1,5	M 16 x 1,5	7	27	1.098.2516.50	1.099.2516.50		
M 25 x 1,5	M 20 x 1,5	7	27	1.098.2520.50	1.099.2520.50		
M 32 x 1,5	M 16 x 1,5	8	34	1.098.3216.50	1.099.3216.50		
M 32 x 1,5	M 20 x 1,5	8	34	1.098.3220.50	1.099.3220.50		
M 32 x 1,5	M 25 x 1,5	8	34	1.098.3225.50	1.099.3225.50		
M 40 x 1,5	M 20 x 1,5	8	43	1.098.4020.50	1.099.4020.50		
M 40 x 1,5	M 25 x 1,5	8	43	1.098.4025.50	1.099.4025.50		
M 40 x 1,5	M 32 x 1,5	8	43	1.098.4032.50	1.099.4032.50		
M 50 x 1,5	M 25 x 1,5	9	55	1.098.5025.50	1.099.5025.50		
M 50 x 1,5	M 32 x 1,5	9	55	1.098.5032.50	1.099.5032.50		
M 50 x 1,5	M 40 x 1,5	9	55	1.098.5040.50	1.099.5040.50		
M 63 x 1,5	M 32 x 1,5	10	65	1.098.6332.50	1.099.6332.50		
M 63 x 1,5	M 40 x 1,5	10	65	1.098.6340.50	1.099.6340.50		
M 63 x 1,5	M 50 x 1,5	10	65	1.098.6350.50	1.099.6350.50		

AG	IG	GL mm	H mm	H mm	Buna-N		VQM	
					20°C – 95°C (-4°F – 208°F)	-60°C – 180°C (-76°F – 356°F)	20°C – 95°C (-4°F – 208°F)	-60°C – 180°C (-76°F – 356°F)
PG 9	PG 7	6	8,8	17	1.098.0907.01	1.099.0907.01		
PG 11	PG 7	6	9	20	1.098.1107.01	1.099.1107.01		
PG 11	PG 9	6	9	20	1.098.1109.01	1.099.1109.01		
PG 13,5	PG 9	6,5	9,5	22	1.098.1309.01	1.099.1309.01		
PG 13,5	PG 11	6,5	9,5	22	1.098.1311.01	1.099.1311.01		
PG 16	PG 9	6,5	9,5	24	1.098.1609.01	1.099.1609.01		
PG 16	PG 11	6,5	9,5	24	1.098.1611.01	1.099.1611.01		
PG 16	PG 13,5	6,5	9,5	24	1.098.1613.01	1.099.1613.01		
PG 21	PG 11	7	10,3	30	1.098.2111.01	1.099.2111.01		
PG 21	PG 13,5	7	10,3	30	1.098.2113.01	1.099.2113.01		
PG 21	PG 16	7	10,3	30	1.098.2116.01	1.099.2116.01		
PG 29	PG 16	8	11,5	40	1.098.2916.01	1.099.2916.01		
PG 29	PG 21	8	11,5	40	1.098.2921.01	1.099.2921.01		
PG 36	PG 21	9	12,5	50	1.098.3621.01	1.099.3621.01		
PG 36	PG 29	9	12,5	50	1.098.3629.01	1.099.3629.01		
PG 42	PG 29	10	13,5	57	1.098.4229.01	1.099.4229.01		
PG 42	PG 36	10	13,5	57	1.098.4236.01	1.099.4236.01		
PG 48	PG 36	10	13,5	64	1.098.4836.01	1.099.4836.01		
PG 48	PG 42	10	13,5	64	1.098.4842.01	1.099.4842.01		

