


Polyamide-Fitting



Material	Polyamide
Protection Category	IP 55
Operating Temperature	-30 °C – +80 °C (-22 °F – +176 °F)
Colours	grey (RAL 7031), black (RAL 9005)

RoHS

- // Raw material according to UL 94
- // Locknut optional
- // Easy disassembly without tools



AG	d mm	D mm	GL mm	H mm	mm	fits to Polyamide- Conduit DN	Number grey	Number black
M 12	6,9	18,7	11	26	15	7	1.533.1200.50	1.533.1201.50
M 16	10,8	21,7	11	26	18	10	1.533.1600.51	1.533.1601.51
M 16	10,9	26	11	26,5	20	12	1.533.1600.50	1.533.1601.50
M 20	14,7	28	11	31	23	14	1.533.2000.51	1.533.2001.51
M 20	15,2	32	13	33	27	17	1.533.2000.50	1.533.2001.50
M 25	18,7	39,5	16	39	34	23	1.533.2500.50	1.533.2501.50
M 32	25,7	46,5	16	43	40	29	1.533.3200.50	1.533.3201.50
M 40	32,7	55,5	16	45,5	50	36	1.533.4000.50	1.533.4001.50
M 50	51,4	67,5	16	47,5	62	48	1.533.5000.50	1.533.5001.50
PG 7	6,9	18,7	11	26	15	7	1.533.0700.14	1.533.0701.14
PG 9	10,3	21,7	11	26	18	10	1.533.0900.14	1.533.0901.14
PG 11	13,3	26	11	26,5	20	12	1.533.1100.14	1.533.1101.14
PG 13,5	15,3	28	11	31	23	14	1.533.1300.14	1.533.1301.14
PG 16	16,6	32	13	33	27	17	1.533.1600.14	1.533.1601.14
PG 21	22,3	39,5	16	39	34	23	1.533.2100.14	1.533.2101.14
PG 29	31,7	46,5	16	43	40	29	1.533.2900.14	1.533.2901.14
PG 36	40,5	55,5	16	45,5	50	36	1.533.3600.14	1.533.3601.14
PG 48	51,7	67,5	16	47,5	62	48	1.533.4800.14	1.533.4801.14