

Polyamide-Fitting DUO-PA


NPT



Material	Polyamide
Seal	NBR
Protection Category	IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) on the cable gland
Operating Temperature	-40 °C – +100 °C (-40 °F – +212 °F)
Colours	black (RAL 9005)



- // 2 in 1 cable gland and conduit fitting
- // Easy disassembly without tools



AG	∅ _{mm}	GL mm	H mm	D mm	∅ _{mm}	fits to Polyamide- Conduit DN	Number
NPT 1/2"	10–14	13	46	29	27	14	1.542.1214.70
NPT 1/2"	07–12	13	46	29	27	14	1.542.1214.71
NPT 3/4"	13–18	14	50	30	33	17	1.542.3417.70
NPT 3/4"	09–16	14	50	30	33	17	1.542.3417.71
NPT 1"	18–24	19	60	39	42	23	1.542.1023.70
NPT 1"	13–20	19	60	39	42	23	1.542.1023.71
NPT 1 1/2"	22–31	20	69	45	53	29	1.542.6429.70

Polyamide-Conduit

Polyamide-Fitting

Metal-Conduit / Metal-Fitting

Metal-Conduit Pro / Metal-Fitting Pro

Accessories Polyamide / Metal