



Material	Polyamide
Seal	NBR
Protection Category	IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) on the cable gland
Operating Temperature	-40 °C – +100 °C (-40 °F – +212 °F)
Colours	black (RAL 9005)



// 2 in 1 cable gland and conduit fitting
 // Easy disassembly without tools

AG	∅ _k mm	GL mm	H mm	D mm	∅ _h mm	fits to Polyamide- Conduit DN	Number
M 16	05–10	8	40	23	22	10	1.542.1610.50
M 16	03–07	8	40	23	22	10	1.542.1610.51
M 20	06–12	10	44	25	24	12	1.542.2012.50
M 20	05–09	10	44	25	24	12	1.542.2012.51
M 20	10–14	10	46	29	27	14	1.542.2014.50
M 20	07–12	10	46	29	27	14	1.542.2014.51
M 25	13–18	11	50	30	33	17	1.542.2517.50
M 25	09–16	11	50	30	33	17	1.542.2517.51
M 32	18–24	11	60	39	42	23	1.542.3223.50
M 32	13–20	11	60	39	42	23	1.542.3223.51
M 40	22–31	13	69	45	53	29	1.542.4029.50
M 40	20–26	13	69	45	53	29	1.542.4029.51
M 50	32–36	13	74	52	60	36	1.542.5037.50
M 50	25–31	13	74	52	60	36	1.542.5037.51
M 63	37–44	14	79	52	68	48	1.542.6350.50
M 63	29–35	14	79	52	68	48	1.542.6350.51
PG 11	05–10	8	40	23	22	10	1.543.1110.14
PG 11	03–07	8	40	23	22	10	1.543.1110.15
PG 13,5	06–12	9	44	25	24	12	1.543.1312.14
PG 13,5	05–09	9	44	25	24	12	1.543.1312.15
PG 16	10–14	10	47	29	27	14	1.543.1614.14
PG 16	07–12	10	47	29	27	14	1.543.1614.15
PG 21	13–16	11	50	30	33	17	1.543.2117.14
PG 21	09–16	11	50	30	33	17	1.543.2117.15
PG 29	18–22	11	60	39	42	23	1.543.2923.14
PG 29	13–20	11	60	39	42	23	1.543.2923.15
PG 36	22–31	13	69	45	53	29	1.543.3629.14
PG 36	20–26	13	69	45	53	29	1.543.3629.15
PG 42	32–36	13	74	52	60	36	1.543.4237.14
PG 42	25–31	13	74	52	60	36	1.543.4237.15
PG 48	37–44	14	79	52	68	48	1.543.6350.14
PG 48	29–35	14	79	52	68	48	1.543.6350.15