

Polyamide-Fitting DUO-MS

NPT



| | |
|-----------------------|---|
| Material | Nickel plated brass |
| Clamping Insert | Polyamide |
| Seal | NBR |
| Protection Category | IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) on the cable gland |
| Operating Temperature | -40 °C – +100 °C (-40 °F – +212 °F) |



- // 2 in 1 cable gland and conduit fitting
- // Easy disassembly without tools

| AG | ∅ mm | GL mm | H mm | D mm | mm | fits to Polyamide-Conduit DN | Number |
|----------|-------|-------|------|------|-------|------------------------------|---------------|
| NPT 1/2" | 10–14 | 13 | 40,5 | 29 | 28/24 | 14 | 1.547.1214.70 |
| NPT 1/2" | 07–12 | 13 | 40,5 | 29 | 28/22 | 14 | 1.547.1214.71 |
| NPT 3/4" | 13–18 | 13 | 44,5 | 30 | 30/30 | 17 | 1.547.3417.70 |
| NPT 3/4" | 09–16 | 13 | 44,5 | 30 | 30/30 | 17 | 1.547.3417.71 |
| NPT 1" | 18–24 | 19 | 50,5 | 39 | 40/40 | 23 | 1.547.1023.70 |
| NPT 1" | 13–20 | 19 | 50,5 | 39 | 40/40 | 23 | 1.547.1023.71 |

Polyamide-Conduit

Polyamide-Fitting

Metal-Conduit / Metal-Fitting

Metal-Conduit Pro / Metal-Fitting Pro

Accessories Polyamide / Metal