




Material	Nickel plated brass
Clamping Insert	Polyamide
Seal	NBR
Protection Category	IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) on the cable gland
Operating Temperature	-40 °C – +100 °C (-40 °F – +212 °F)

- // 2 in 1 cable gland and conduit fitting
- // Easy disassembly without tools



AG	∅ _k mm	GL mm	H mm	D mm	∅ _h mm	fits to Polyamide- Conduit DN	Number
M 16	05–10	6	36	23	20/20	10	1.547.1610.50
M 16	03–07	6	36	23	20/20	10	1.547.1610.51
M 20	10–14	6	39,5	25	24/22	12	1.547.2012.50
M 20	07–12	6	39,5	25	24/22	12	1.547.2012.51
M 20	10–14	6	40,5	29	28/24	14	1.547.2014.50
M 20	07–12	6	40,5	29	28/24	14	1.547.2014.51
M 25	13–18	7	44.5	30	30/30	17	1.547.2517.50
M 25	09–16	7	44.5	30	30/30	17	1.547.2517.51
M 32	18–24	8	50,5	39	40/40	23	1.547.3223.50
M 32	13–20	8	50,5	39	40/40	23	1.547.3223.51
M 40	22–31	8	56,5	45	50/50	29	1.547.4029.50
M 40	20–26	8	56,5	45	50/50	29	1.547.4029.51
M 50	32–36	9	57,5	52	57/57	36	1.547.5037.50
M 50	25–31	9	57,5	52	57/57	36	1.547.5037.51
M 63	37–44	10	60,5	52	68/64	48	1.547.6350.50
M 63	29–35	10	60,5	52	68/64	48	1.547.6350.51
PG 11	05–10	6	36	23	20/20	10	1.548.1110.01
PG 11	03–07	6	36	23	20/20	10	1.548.1110.15
PG 13,5	6–12	6,5	39,5	25	24/22	12	1.548.1312.01
PG 13,5	5–9	6,5	39,5	25	24/22	12	1.548.1312.15
PG 16	10–14	6,5	40,5	29	28/24	14	1.548.1614.01
PG 16	07–12	6,5	40,5	29	28/24	14	1.548.1614.15
PG 21	13–16	7	44.5	30	30/30	17	1.548.2117.01
PG 21	09–16	7	44.5	30	30/30	17	1.548.2117.15
PG 29	18–22	8	50,5	39	40/40	23	1.548.2923.01
PG 29	13–20	8	50,5	39	40/40	23	1.548.2923.15
PG 36	22–28	8	56,5	45	50/50	29	1.548.3629.01
PG 36	20–26	8	56,5	45	50/50	29	1.548.3629.15
PG 42	32–36	9	57,5	52	57/57	36	1.548.4237.01
PG 42	25–31	9	57,5	52	57/57	36	1.548.4237.15
PG 48	37–44	10	60,5	52	64/64	48	1.548.4850.01
PG 48	29–35	10	60,5	52	64/64	48	1.548.4850.15