


Metal-Fitting Pro S



Material	Nickel plated brass
Protection Category	IP 67
Operating Temperature	-20 °C – +80 °C (-4 °F – +176 °F)

RoHS

- // Swivel conduit fitting
- // Locknut optional



AG	d mm	D mm	GL mm	H mm	1 mm	2 mm	fits to Metal- Conduit Pro DN	Number
M 12	16,5	24,5	10	34	20	22	-/09	1.573.1260.50
M 16	16,5	24,5	10	35	20	22	10/11	1.573.1660.51
M 16	19	29,2	10	37	20	22	12/13	1.573.1660.50
M 20	22	32,6	13	41	27	29	16	1.573.2060.50
M 25	27,5	38,8	15	44	33	35	21	1.573.2560.50
M 32	34,5	50	15	51	43	45	27/26	1.573.3260.50
M 40	43,5	60	16	54	52	54	35	1.573.4060.50
M 50	49,5	69,3	18	64	60	63	40	1.573.5060.50
M 63	62	85	20	76	74	77	51	1.573.6360.50
PG 7	16,5	24,5	10	34	20	22	-/09	1.573.0760.14
PG 9	16,5	24,5	10	34	20	22	10/11	1.573.0960.14
PG 11	19	29,2	11,5	35	24	26	12/13	1.573.1160.14
PG 13,5	22	32,6	13	37	27	29	16	1.573.1360.14
PG 16	22	32,6	13	41	27	29	16	1.573.1660.14
PG 21	27,5	38,8	15	44	33	35	21	1.573.2160.14
PG 29	34,5	50	15	51	43	45	27/26	1.573.2960.14
PG 36	43,5	60	16	54	52	54	35	1.573.3660.14
PG 42	49,5	69,3	18	64	60	63	40	1.573.4260.14
PG 48	62	85	20	76	74	77	51	1.573.4860.14
NPT 1/4"	16,5	24,5	10	35	20	22	10/11	1.573.1460.70
NPT 3/8"	19	29,2	11,5	37	20	22	12/13	1.573.3860.70
NPT 1/2"	22	32,6	13	41	27	29	16	1.573.1260.70
NPT 3/4"	27,5	38,8	15	44	33	35	21	1.573.3460.70
NPT 1"	34,5	50	15	51	43	45	26/27	1.573.1060.70
NPT 1 1/4"	43,5	60	16	54	52	54	35	1.573.5460.70
NPT 1 1/2"	49,5	69,3	18	64	60	63	40	1.573.6460.70
NPT 2"	62	85	20	76	74	77	51	1.573.2060.70