


**NPN SILICON PLANAR SWITCHING TRANSISTORS**

**2N2221 2N2222**



**TO-18  
Metal Can Package**

**General Purpose Transistor**

**ABSOLUTE MAXIMUM RATINGS**

DESCRIPTION	SYMBOL	VALUE	UNIT
Collector Emitter Voltage	$V_{CEO}$	30	V
Collector Base Voltage	$V_{CBO}$	60	V
Emitter Base Voltage	$V_{EBO}$	5	V
Collector Current Continuous	$I_C$	800	mA
Power Dissipation @ $T_a=25^\circ\text{C}$ Derate Above $25^\circ\text{C}$	$P_D$	500 2.85	mW mW/°C
Power Dissipation @ $T_c=25^\circ\text{C}$ Derate Above $25^\circ\text{C}$	$P_D$	1.2 6.85	W mW/°C
Operating And Storage Junction Temperature Range	$T_j, T_{stg}$	- 65 to +200	°C


**ELECTRICAL CHARACTERISTICS ( $T_a=25^\circ\text{C}$  unless specified otherwise )**

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Collector Emitter Voltage	$*V_{CEO}$	$I_C=10\text{mA}, I_B=0$	30			V
Collector Base Voltage	$V_{CBO}$	$I_C=10\mu\text{A}, I_E=0$	60			V
Emitter Base Voltage	$V_{EBO}$	$I_E=10\mu\text{A}, I_C=0$	5			V
Collector Cut Off Current	$I_{CBO}$	$V_{CB}=50\text{V}, I_E=0$			10	nA
		$V_{CB}=50\text{V}, I_E=0,$ $T_a=150^\circ\text{C}$			10	$\mu\text{A}$
Collector Cut Off Current	$I_{EBO}$	$V_{EB}=3\text{V}, I_C=0$			10	nA

			<b>2N2221</b>	<b>2N2222</b>	
<b>DC Current Gain</b>	$h_{FE}$	$*I_C=0.1\text{mA}, V_{CE}=10\text{V}$	>20	>35	
		$I_C=1\text{mA}, V_{CE}=10\text{V}$	>25	>50	
		$*I_C=10\text{mA}, V_{CE}=10\text{V}$	>35	>75	
		$*I_C=150\text{mA}, V_{CE}=10\text{V}$	40 - 120	100 - 300	
		$*I_C=150\text{mA}, V_{CE}=1\text{V}$	>20	>50	
		$*I_C=500\text{mA}, V_{CE}=10\text{V}$	>20	>30	

**\*Pulse Test: Pulse Width  $\leq 300\text{ms}$ , Duty Cycle  $\leq 2\%$**

2N2221\_2222Rev\_1 310303E



TO-18  
Metal Can Package

ELECTRICAL CHARACTERISTICS ( $T_a=25^\circ\text{C}$  unless specified otherwise)

SMALL SIGNAL CHARACTERISTICS

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Collector Emitter Saturation Voltage	$*V_{CE(sat)}$	$I_C=150\text{mA}, I_B=15\text{mA}$			0.4	V
		$I_C=500\text{mA}, I_B=50\text{mA}$			1.6	V
Base Emitter Saturation Voltage	$*V_{BE(sat)}$	$I_C=150\text{mA}, I_B=15\text{mA}$			1.3	V
		$I_C=500\text{mA}, I_B=50\text{mA}$			2.6	V
Transition Frequency	$**f_T$	$I_C=20\text{mA}, V_{CE}=20\text{V},$ $f=100\text{MHz}$	250			MHz
Output Capacitance	$C_{obo}$	$V_{CB}=10\text{V}, I_E=0,$ $f=100\text{KHz}$			8.0	pF
Input Capacitance	$C_{ibo}$	$V_{BE}=0.5\text{V}, I_C=0,$ $f=100\text{KHz}$			30	pF

SWITCHING TIME


DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Delay Time	$t_d$	$I_C=150\text{mA}, I_{B1}=15\text{mA},$ $V_{CC}=30\text{V}, V_{BE(off)}=0.5\text{V}$			10	ns
Rise Time	$t_r$				25	ns
Storage Time	$t_s$	$I_C=150\text{mA}, I_{B1}=$ $I_{B2}=15\text{mA}, V_{CC}=30\text{V}$			225	ns
Fall Time	$t_f$				60	ns

\*Pulse Test: Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2\%$

\*\*  $f_T$  is defined as the frequency at which  $|h_{fe}|$  extrapolates to unity


**TO-18  
Metal Can Package**

**TO-18 Metal Can Package**



All dimensions in mm.

DIM	MIN	MAX
A	5.24	5.84
B	4.52	4.97
C	4.31	5.33
D	0.40	0.53
E	—	0.76
F	—	1.27
G	—	2.97
H	0.91	1.17
J	0.71	1.21
K	12.70	—
L	45 DEG	



**PIN CONFIGURATION**

- 1. EMITTER
- 2. BASE
- 3. COLLECTOR

**Packing Detail**

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-18	1K/polybag	350 gm/1K pcs	3" x 7.5" x 7.5"	5K	17" x 15" x 13.5"	80K	34 kgs

### Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of  
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.  
Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119  
email@cdil.com www.cdilsemi.com