

SIEMENS

Product data sheet

3TX7004-1MF00



Abb. ähnlich / similar picture

OUTPUT INTERFACE TWO-TIER TERMINAL-TYPE
COUPLING RELAY 1N0,
AC/DC 230V SCREW TERMINAL WIDTH 6.2MM

General technical details:

Type of voltage	AC/DC
Supply voltage frequency / for auxiliary and control current circuit / rated value	
• minimum	50 Hz
• maximum	60 Hz
Control supply voltage	
• at 50 Hz / for AC / rated value	
• minimum	230 V
• maximum	230 V
• at 60 Hz / for AC / rated value	
• minimum	230 V
• maximum	230 V
• for DC / rated value	
• minimum	230 V
• maximum	230 V
Number of NC contacts / for auxiliary contact	0
Number of NO contacts / for auxiliary contact	1
Number of change-over switches / for auxiliary contact	0
Switching behaviour	monostable

Mechanical design:	
Design of the electrical connection	screw-type terminals
Design of the electrical connection / Jumper socket	No
Design of the relay operating mechanism	poled
Design of the switching function	NO contact
• guided	No
Product component / Jumper socket	No
Width	6.2 mm
Height	60 mm
Depth	62 mm
Ambient conditions:	
Protection class IP	IP20
last change:	10/31/2006

Technical Assistance:	Telephone:	+49 (0) 911-895-5900 (8°° - 17°° CET)
	Fax:	+49 (0) 911-895-5907
	E-Mail:	technical-assistance@siemens.com
	Internet:	www.siemens.de/lowvoltage/technical-assistance