

**MCE MCE II PC 28 MF/M**



Sample photo

**Order symbol:** MCE II PC 28 MF/M      **EAN:** 6418074077653  
**Product nbr:** 7252181      **EI. number:**  
**Description:** DIN rail modular enclosure, PC Finland: 3424097  
**Remarks:**

Including: Modular component enclosure with TPE gaskets, mounted DIN 35-rails, three mounted PEN 10 mm<sup>2</sup> bars, Multi-FEM and FEM membrane cable glands, module marking stripes and pockets, module cover plate, wall mount cover plugs and mounting instructions.

Dimensions:	Length	Width	Height	Accessories:
mm:	430	306	145	FP 26128      Fastening lug set
inch:	16.9	12.0	5.7	FP 26127      Fastening lug set

Materials:	Rating:
<b>Material:</b> Polycarbonate	Ingress Protection (EN 60529): IP65
<b>Base colour:</b> RAL 7035 -light grey	Impact Resistance (EN 62262): IK08
<b>Cover screws material:</b> Polyamide	Electrical insulation: Totally insulated
<b>Cover colour:</b> Smoked grey	Halogen free (DIN/VDE 0472, Part 815): 1
<b>Cover screws colour:</b> Grey	UV resistance: UL 508
<b>Gasket material:</b> TPE	Flammability Rating: UL 746C 5"
	Glow Wire Test (IEC 695-2-1) °C: 960

Temperatures:	Certificates:
<b>Temperature °C (short term):</b> -40 ... 120 °C	SGS Fimko
<b>Temperature °C (continuous):</b> -40 ... 80 °C	Gost R
<b>Temperature °F (short term):</b> -40 ... 250 °F	
<b>Temperature °F (continuous):</b> -40 ... 175 °F	

Accessories:
FP A 26133      Front plate, aluminium

