

**MCE MCE II PC 28 MF/FL**



Sample photo

**Order symbol:** MCE II PC 28 MF/FL      **EAN:** 6418074071040  
**Product nbr:** 7252215      **EI. number:**  
**Description:** DIN rail modular enclosure, PC Finland: 3424144  
**Remarks:**

Including: Modular component enclosure with TPE gaskets, mounted DIN 35-rails, three mounted PEN 10 mm<sup>2</sup> bars, Multi-FEM and FEM membrane cable glands, module marking stripes and pockets, module cover plate, wall mount cover plugs and mounting instructions.

Dimensions:	Length	Width	Height	Accessories:	
mm:	430	306	145	FP 26128	Fastening lug set
inch:	16.9	12.0	5.7	FP 26127	Fastening lug set

Materials:		Rating:	
<b>Material:</b>	Polycarbonate	Ingress Protection (EN 60529): IP65	
<b>Base colour:</b>	RAL 7035 -light grey	Impact Resistance (EN 62262): IK08	
<b>Cover screws material:</b>	Polyamide	Electrical insulation: Totally insulated	
<b>Cover colour:</b>	Smoked grey	Halogen free (DIN/VDE 0472, Part 815): 1	
<b>Cover screws colour:</b>	Grey	UV resistance: UL 508	
<b>Gasket material:</b>	TPE	Flammability Rating: UL 746C 5"	
		Glow Wire Test (IEC 695-2-1) °C: 960	

Temperatures:		Certificates:	
<b>Temperature °C (short term):</b>	-40 ... 120 °C	SGS Fimko	
<b>Temperature °C (continuous):</b>	-40 ... 80 °C	Gost R	
<b>Temperature °F (short term):</b>	-40 ... 250 °F		
<b>Temperature °F (continuous):</b>	-40 ... 175 °F		

Accessories:	
FP A 26133	Front plate, aluminium

