

CARDMASTER PC 30/25-C3



Sample photo

Order symbol: PC 30/25-C3
Product nbr: 7520031
Description: Enclosure, PC
Remarks: With aluminium front plate

EAN: 6418074005854
EI. number:
 Finland: 3420830
 Electric No. 8212016596
 Denmark:
 Electric No. Sweden: 7520031

Including: Base, terminal compartment cover with EPDM gasket and screws for mounting plate/DIN-rail. -3 and -L3 versions: Transparent cover with PUR gasket, hinges, locking devices; FC version: Closed PC frame front plate with PUR gasket and cover screws.

Dimensions:	Length	Width	Height	Accessories:
mm:	314	260	95	FP 30/25 Front plate (aluminium)
inch:	12.4	10.2	3.7	FC PC 30/25 Frame of PC front plate
Materials:				Rating:
Material:	Polycarbonate			Impact Resistance (EN 62262): IK07
Base colour:	RAL 7035 -light grey			Electrical insulation: Totally insulated
Gasket material:	EPDM			Halogen free (DIN/VDE 0472, Part 815): 1
Temperatures:				UV resistance: UL 508
Temperature °C (short term):	-40 ... 120 °C			Flammability Rating: UL 746C 5"
Temperature °C (continuous):	-40 ... 80 °C			Glow Wire Test (IEC 695-2-1) °C: 960
Temperature °F (short term):	-40 ... 250 °F			NEMA Class: NEMA 1, 3, 3R, 12, 13
Temperature °F (continuous):	-40 ... 175 °F			Certificates:
Accessories:				SGS Fimko
MP 30/25	Mounting plate			Gost R

