


7924A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable



For more Information
please call

1-800-Belden1



Description

24 AWG Bonded-Pairs stranded (7x32) tinned copper conductors, polyolefin insulation, industrial grade sunlight- and oil-resistant PVC jacket. Sequential marking at two foot intervals.

Suitable Applications (Overall):

Suitable Applications

Industrial Ethernet Cable, Harsh Environments, 350MHz Enhanced Category 5e, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, CMX - Outdoor, RJ-45 Compatible, Flexible Applications

Physical Characteristics (Overall):

Conductor:

AWG

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
4.000	24	7x32	TC - Tinned Copper	0.022

Insulation:

Insulation Material

Insulation Material	Wall Thickness (in.)	Dia. (in.)
PO - Polyolefin	0.008	0.037

Outer Shield:

Outer Shield Material

Outer Shield Material
Unshielded

Outer Jacket:

Outer Jacket Material

Outer Jacket Material	Nom. Wall Thickness (in.)
Industrial Grade PVC - Polyvinyl Chloride	0.030

Overall Cabling:

Overall Nominal Diameter: 0.242 in.

Pair:

Pair Color Code Chart

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Mechanical Characteristics (Overall):

Operating Temperature Range	-40°C To +75°C
Storage Temperature Range	-25°C To +75°C
Installation Temperature Range	-25°C To +75°C
Bulk Cable Weight:	26 lbs/1000 ft.
Max. Recommended Pulling Tension:	40 lbs.
Min. Bend Radius (Install)/Minor Axis:	0.250 in.

7924A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards:

NEC/(UL) Specification	CMR, CMX-Outdoor, UL444
CEC/C(UL) Specification	CMR
IEC Specification	11801 Category 5e Patch
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	01/01/2004
TIA/EIA Specification	568-B.2 Category 5e Patch
Other Specification	NEMA WC-63.1 Category 5, ICEA 661, Category 5e Patch, UL verified to TIA/EI-568-B.2, Category 5e

Flame Test:

UL Flame Test	UL1666 Riser
CSA Flame Test	FT4

Suitability:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes
Sunlight Resistance	Yes
Oil Resistance	Yes

Plenum/Non-Plenum:

Plenum (Y/N)	No
--------------	----

Electrical Characteristics (Overall):

Nom. Mutual Capacitance

Capacitance (pF/ft)
15.000

Nominal Velocity of Propagation

VP (%)
70

Maximum Capacitance Unbalance (pF/100 m) 66

Maximum Delay

Delay (ns/100 m)
510.000

Max. Delay Skew

Delay Skew (ns/100 m)
25

Maximum Conductor DC Resistance

DCR @ 20°C (Ohm/100 m)
9.000

Max. Operating Voltage - UL

Voltage
300 V RMS

Maximum DCR Unbalanced

DCR Unbalance @ 20°C (%)
3.000

Electrical Characteristics-Premise (Overall):

Premise Cable Electrical Table 1

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. PSACR (dB)	Min RL (dB)
1	2.400	65.300	65.300	62.900	20.000
4	4.800	56.300	56.300	51.500	23.000

7924A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable

8	6.800	51.800	51.800	45.000	24.500
10	7.700	50.300	50.300	42.600	25.000
16	9.700	47.300	47.300	37.500	25.000
20	11.000	45.800	45.800	34.800	25.000
25	12.400	44.300	44.300	31.900	24.300
31.250	13.900	42.900	42.900	29.000	23.600
62.500	20.200	38.400	38.400	18.300	21.500
100	26.000	35.300	35.300	9.200	20.100
155	33.200	32.500	32.500	0	19.000
200	38.400	30.800	30.800		19.000
250	43.700	29.300	29.300		18.000
300	48.600	28.200	28.200		18.000
310	49.500	27.900	27.900		18.000
350	53.200	27.200	27.200		17.000

Premise Cable Electrical Table 2

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 12	105 ± 10	63.800	60.800
4	100 ± 12	100 ± 10	51.700	48.700
8	100 ± 12	100 ± 10	45.700	42.700
10	100 ± 12	100 ± 10	43.800	40.800
16	100 ± 12	100 ± 10	39.700	36.700
20	100 ± 12	100 ± 10	37.700	34.700
25	100 ± 15	100 ± 10	35.800	32.800
31.250	100 ± 15	100 ± 10	33.900	30.900
62.500	100 ± 15	100 ± 10	27.800	24.800
100	100 ± 18	100 ± 10	23.800	20.800
155	100 ± 18	100 ± 10	19.900	16.900
200	100 ± 20	100 ± 10	17.700	14.700
250	100 ± 20	100 ± 10	15.800	12.800
300	100 ± 20	100 ± 10	14.200	11.200
310	100 ± 20	100 ± 10	13.900	10.900
350	100 ± 22	100 ± 10	12.900	9.900

Notes (Overall):

Notes US Patents 5, 606, 151; 5, 734, 126; 5, 763, 823. EtherNet/IP is a trademark of ControlNet International, Ltd. under license by Open DeviceNet Vendor Association, Inc. Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581.

PUT UPS AND COLORS:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7924A 0021000	1,000 FT	30.000 LB	RED	C	4 PR #24 PP PVC RED
7924A 0101000	1,000 FT	30.000 LB	BLACK	C	4 PR #24 PP PVC BLK
7924A 0102000	2,000 FT	58.000 LB	BLACK	C	4 PR #24 PP PVC BLK
7924A 1NH1000	1,000 FT	30.000 LB	TEAL 1NH	C	4 PR #24 PP PVC TEAL1NH

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 5 Revision Date: 05-14-2007

© 2008 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of

7924A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable

such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory; and China Ministry of Information Industry order#39 (China RoHS). EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.