

## ARCA 302015



Sample photo

**Order symbol:** ARCA 302015  
**Product nbr:** 8120002  
**Description:** Cabinet, PC  
**Remarks:** 1-point locking

**EAN:** 6418074079138  
**EI. number:**  
 Finland: 3423044  
 Electric No. 8212091003  
 Denmark:  
 Electric No. Sweden: 2500110

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

| Dimensions:                         |                               |       |        | Accessories:   |   |
|-------------------------------------|-------------------------------|-------|--------|--|---|
|                                     | Length                        | Width | Height |  |   |
| <b>mm:</b>                          | 300                           | 200   | 150    | MPP ARCA 3020  | Mounting plate perforated (250x150x2 mm - 26x11 mm)     |
| <b>inch:</b>                        | 11.8                          | 7.9   | 5.9    | MPMP ARCA 3020                                       | Mounting plate multiperforated (250x150x2 mm - □3.6 mm) |
| Materials:                          |                               |       |        | MPX ARCA 3020  | Mounting plate (250x150 mm)                             |
| <b>Material:</b>                    | Polycarbonate                 |       |        | DRS ARCA 302015                                      | DIN rail frame set                                      |
| <b>Base colour:</b>                 | RAL 7035 -light grey          |       |        | DRS ARCA 302021                                      | DIN rail frame set                                      |
| <b>Cover colour:</b>                | RAL 7035 -light grey          |       |        | IDS ARCA 3020  | Inner door set  |
| <b>Gasket material:</b>             | Polyurethane                  |       |        | PMK ARCA 20  | Pole mounting kit                                       |
| Temperatures:                       |                               |       |        | RCS ARCA 3020  | Rain canopy set   |
| <b>Temperature °C (short term):</b> | -40 ... 120 °C                |       |        | SBK ARCA 20  | Support bar kit   |
| <b>Temperature °C (continuous):</b> | -40 ... 80 °C                 |       |        | SBK ARCA 30  | Support bar kit   |
| <b>Temperature °F (short term):</b> | -40 ... 250 °F                |       |        | Rating:  |   |
| <b>Temperature °F (continuous):</b> | -40 ... 175 °F                |       |        | Ingress Protection (EN 60529): IP66                  |   |
| Accessories:                        |                               |       |        | Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C |   |
| MPS ARCA 3020                       | Mounting plate (250x150x2 mm) |       |        | Electrical insulation: Totally insulated             |   |
|                                     |                               |       |        | Halogen free (DIN/VDE 0472, Part 815): 1             |   |
|                                     |                               |       |        | UV resistance: UL 508                                |   |
|                                     |                               |       |        | Flammability Rating: UL 94 5VA                       |   |
|                                     |                               |       |        | Glow Wire Test (IEC 695-2-1) °C: 960                 |   |
|                                     |                               |       |        | Certificates:  |   |
|                                     |                               |       |        | SGS Fimko  |   |
|                                     |                               |       |        | Gost R   |   |

